

2001 Alpena County Remonumentation

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Alpena

(County)

Located in:

Corner Code #

1. Public Land Survey

T 30NR 07E

M-9

X T 30NR 08E

A-9

T R

T R

2. Property Controlling
In Section

S T R

S T R

3. Miscellaneous
Property in Sec.

S T R

S T R

4. Lot No. _____, Recorded Plat _____

5. Private Claims _____

I, Wayne T. Lewis, in a field survey on 2-24-01, 18X, do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and for that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law, established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

1839: Lewis Clason set post and witnessed

1908: Unknown surveyor for Alpena Co. Road Commission, set large cedar stake in west wheel track, and witnessed

1930-1950: Marcus Schaff, P.S., set iron, no witnesses given

1973: Alpena Co. Road Commission found 2" gas pipe & set 1/2" rod above and witnessed

1991: D.R. MacNeill, P.S. used corner, and recorded surveys in Liber 292 of Deeds, page 594, no witnesses or monumentation given

1996: T.L. Fabis, P.S., found 1/2" iron rod and witnessed

1999: Alpena Co. Road Commission, found 2" gas pipe w/1/2" rebar, and witnessed

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Found 1/2" rerod w/cap #27461 in mon. box, 7.5' North of c/l of gravel drive to West, and 3' South of c/l of gravel drive to the East

This corner is accepted as the best evidence of the location of the original corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

2001: Placed 3" Alpena County Remonumentation Cap, stamped to identify the corner, on exist. 1/2" rerod with cap in mon. box

Witnesses:

N 50° E 68.72' 11" White Pine (set tag #41922)

S 45° E 50.24' 12" Maple (Ex. Tag #31591)

S 65° W 54.93' Power Pole (Ex. Tag #31591)

N 60° W 62.12' 6" White Pine (ex. tag #31591)

Signed by

Surveyor's Michigan License No. 41922Date September 14, 2001

L-2 P-371

09/18/2001 08:54A

Page: 1 of 1

Kathy J. Matash, Register Alpena Co., MI LDC 8.00


SURVEY &
REMONUMENTATION

FEB 01 2002

SECTION

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6	5	4	3	2	1							
3													
4	7	0	9	10	11	12							
5													
6	18	17	16	15	14	13							
7													
8	19	20	21	22	23	24							
9													
10	30	29	28	27	26	25							
11													
12	31	32	33	34	35	36							
13													

P.A. 345 ALPENA COUNTY
PEER APPROVED 08-06-01*W.T. Lewis*FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 28, 1971
REVISED MAY 14, 1975
REVISED JAN. 1983
REVISED OCT. 1990