

COPY

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A. 1970

RECORDED
At 9:20 AM
of 12:00 PM
Page 477
Charles E. Schmelting
REGISTER OF DEEDS

REGISTER OF DEEDS STAMP AND
FILING NUMBER

CORNER CODE NUMBER

LOCATED IN:-

FOR CORNERS OF:-

1. PUBLIC LAND SURVEY T. 42 N. 26 W. 26

2. PROPERTY CONTROL N. S. R. W. 26

3. MISCELLANEOUS T. N. S. R. W. 26

4. LOT NO. , RECORDED PLAT

5. PRIVATE CLAIMS

I, Robert E. Schmelting, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on May 22, 1980, established, and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on May 22, 1980, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:
Section corner common to Sections 11, 12, 13 and 14, T42N, R26W, Marquette County.
Original Bearing Trees:
Tamarack 10" S44°W 25 (old stump with lower face evident this date. Charles Walkner observed iron marks within face on his visit in 1968.)
Cedar 12" N39°E 10 (now a moss covered mound).

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:
Observed above original evidence and found in place a 1 1/2" x 2' iron bar below ground surface. Found old 3" squared cedar post 1 1/2 feet south.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:
Replaced above iron bar with a 1" diameter 4' long galvanized iron pipe with brass cap thereon stamped with appropriate identification and left 3" cedar post in place.
Made new witnesses as follows:

White Cedar 6" N58°E 24.0 feet to E tree (Scribed: S12 T42N R26W NBT)
Tamarack 5" S41°E 21.2 feet to E tree (Scribed: S13 T42N R26W NBT)
White Cedar 5" S22°W 23.7 feet to E tree (Scribed: S14 T42N R26W NBT)
Tamarack 5" N71°W 13.0 feet to E tree (Scribed: S11 T42N R26W NBT)

All bearings magnetic. Assisted by Charles Walkner and James Okraszewski.

SIGNED BY: Robert E. Schmelting
SURVEYOR'S MICHIGAN REGISTRATION NO. 8317
FOR STATE AND UNITED STATES AGENCIES:
SIGNED BY: _____
CHIEF OF SURVEY PARTY
DATE: _____
MICHIGAN REGISTERED LAND SURVEYOR
DATE: _____

