

REVISIONS	NO.	DATE	BY
	1	8-27-57	W.A.L.
	2		
	3		
	4		
	5		
	6		

REVIEWED BY SECTIONS	DATE	APPROVED BY
ARCHITECTURAL	9-17-57	
ENGINEERING	11 Sept 57	
LANDSCAPE	9-17-57	

DESIGNED BY J.D. GREENWOOD
 DRAWN BY J.W.F.
 TRACED BY W.T.
 CHECKED BY [Signature]
 DATE 9-17-57

ROOMS	FLOOR	BASE	WALLS	CEILING	VARNISHED	STAINED	PAINTED
Women's Toilet	Concrete	Tile	Tile & Wood	Stained Birch			
Men's Toilet							
Shower (Men's)			Tile	Con. with S.			Ceiling
Laundry		None	Wood				Walls & Ceiling

NOTES:
 Interior Finish:
 Finish to be silver gray stain manufactured by The Pomine Paint and Varnish Co. known as Silver Gray S.S. Paste #221. The paste is mixed with a solution of pentachlorophenol, as specified in list of materials, with some black oxide for darker shades or gray.
 Exposed roof rafters and trim, top of plate to be a dark shade of gray. Roof and wall boards to be left natural wood color finished with two (2) coats of Semiac.
 Finish all stained surface with two (2) coats of Semiac (Semiac manufactured by U.S. Pigwood Corp.)
 Wax all wall surfaces after Semiac finish is applied.
 Exterior Finish:
 Finish rough sawn wavy siding, rafter tails, lookout, posts and wood work with a light brown stain made of a solution of pentachlorophenol as specified in list of materials and brown amber pigment ground in oil. Proportion of mix to be determined on the job striving to obtain a light transparent shade of brown.
 Two (2) coats minimum required.
 Roof:
 Wood shingles to be stained with pentachlorophenol using sufficient burnt umber to obtain a dark brown color (by the emersion method)

