



NOTES

Concrete Mix to be 1:2:4. Floor Slab to be poured in small Areas and finished with a smooth troweled surface pitched toward Drains. Walls to have 1/4\"/>

Sash, Toilet Stalls and Preswood Wainscot to be painted with a mixture of Preservative + lead + oil paint. Exterior Trim, Doors, Shingles, Louvers and interior Wall Sheathing above Wainscot to given 2 coats of a mixture of clear preservative and oil stains. All Plumbing + Electrical work to be installed under supervision of 1st class mechanics and all local, State and National Codes to be followed.

DEPARTMENT OF THE INTERIOR NATIONAL PARK SERVICE And MICHIGAN DEPARTMENT OF CONSERVATION CO - OPERATING			
BRANCH OF PLANNING	STATE PARK DIVISION	SHEET NO. 1	
SYMBOL	HARDWICK PINES S.P. #8	FILE NO.	
NUMBER	TOILET BUILDING	DRAWN BY	
DATE	OTSEGO LAKE STATE PARK	DESIGNED	
DATE		PROJECT SUPERINTENDENT	DATE 6-4-35
DATE		FIFTH REGIONAL INSPECTOR	DATE
DATE		FIFTH REGIONAL OFFICER N.P.S.	DATE

A-101 Not built