

SURVEY &
REMONUMENTATION

MAR 04 1999

LAND CORNER RECORDATION CERTIFICATE

SECTION

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

1997 Alcona County Remonumentation

FOR CORNERS OF--:

LOCATED IN--:

CORNER CODE NUMBER

1. PUBLIC LAND SURVEY_____ T. 25N N. 5E E. S., R. W.

NE cor. S. 31
C-11

2. PROPERTY CONTROLL-
ING IN SECTION_____ ,T. _____ N. S., R. _____ E. W.

3. MISCELLANEOUS
PROPERTY IN SECTION_____ ,T. _____ N. S., R. _____ E. W.

4. LOT NO. _____ , RECORDED PLAT _____

5. PRIVATE CLAIMS _____

APPROVED LAND CORNER
P A 345 of 1990
ALCONA COUNTY

Date 7/24/97
County Rep. Doris A. Gauthier

RECORDED

Date September 8, 1997
REMON LIBER 1 PAGE 253

2:20 Time PM

Doris A. Gauthier
Doris A. Gauthier
REGISTER OF DEEDS
REGISTER OF DEEDS STAMP AND
FILING NUMBER

I, John F. Oliver do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above (identified with circles on index code diagram - over) were, in a field survey on Aug. 20, 1997, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on 1997, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

1845: G.L.O. - set post and referenced

1906: E. Chapelle - no description of cor.

1933: Dependent resurvey - fd. wooden post 4 x 4 x 16 ins. and remains of orig. wit. tree - w. pine stump 18" / N 77°W / 10 set 6" x 24" conc. mon w brass tablet

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

fd. Dependent resurvey conc. mon. and orig. wit. tree stump

accepted as the true position of the corner

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Corner is 6" x 24" conc. mon. w brass tablet

referenced: w. pine stump 18" / N 50°W / 6.6 feet (orig.)
w. pine stump 40" / S 35°E / 34.9 feet (Dependent resurvey)
10" maple / S 70°E / 21.72'
cedar post / S 65°E / 1.0'

SIGNED BY _____ DATE _____

SURVEYOR'S MICHIGAN REGISTRATION NO. 19840

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____

CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY _____ DATE _____

MICHIGAN REGISTERED LAND SURVEYOR

(SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. _____