

Approved by Alger County
Land Survey Remonumentation
Peer Group Under Act 345 of
P.A. of 1990 On 4-8-1995

Gerald Wilson
Chairman

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

4-294

For corners in

Alger

(County)

Located In:

Corner Code #

1. Public Land Survey

T 45N R 21W

L1

T R

T R

T R

T R

**SURVEY &
REMONUMENTATION**

MAY 10 1995

COMMISSION

FILED

9:00 a.m.

APR 20 1995

DONALD W. HARRIS
REGISTER

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat

5. Private Claims

	A	B	C	D	E	F	G	H	I	J	K	L	A
2	6	5	4	3	2	1							
3													
4	7	8	9	10	11	12							
5													
6	18	17	16	15	14	13							
7													
8	19	20	21	22	23	24							
9													
10	30	29	28	27	26	25							
11													
12	31	32	33	34	35	36							
13													

I, Robert L. Jamros, in a field survey on December 08, 1994, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

L1: PLS-William A. Burt, DS, 1841, Set Qr. Section Post- Sugar 10", N.65 E., 39 links, Sugar 30", N.29 W., 7 links. Alger County Road Commission Records, George L. Depew, Alger County Surveyor, 1918, Set Corner at equal distance on line between Section corner to east and Section corner to west. No references given. USDA-Forest Service, 1982, recovered monument box at centerline of intersection of M-94 and County Road 283., Gregory W. Asher, RLS, 1984, U.S.D.A. Forest Service recovered monument box could not open. Accepted Center of monument box as the best available evidence of the corner position., References: Pwr.Pole, N20E., 68.6 ft., Maple 9", S39E., 82.4 ft., Maple 7", S13W., 73.5 ft., Maple 12", N43W., 178.5 ft., Filing No. 3-199, Alger County Records. Gary E. Koepke, RLS, 1990, Found boat spike in monument box near existing centerline of M-94 at County Road to north. References: N20E., 68.54 ft., Tag in P.Pole., S39E., 82.50 ft., Tag in 9" Maple., S13W., 73.50 ft., Nail in 7" Maple., N40E., 53.05 ft., Tag in post #283., S30W., 60.20 ft., Tag in 2" Birch, Filing No. 4-77, Alger County Records.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

L1: Found Boatspike in monument box near the centerline of State Highway M-94 and at centerline of County Road north. Verified witnesses of the 1984 and 1990 reports to be in agreement with corner position. Distances, 1984 report, east and west to other corners, agrees well with record distances. Corner position is accepted as a careful and faithful reestablishment of the position of the original corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

L1: Set 2 1/4" x 15" Alum. Monument w/ 3 1/4" Alum. cap over top of existing boat spike stamped to identify corner position. Renewed existing reference trees w/ BT signs and paint. Set PK nails for measure w/ Alum. I.D. washers in the following reference trees. Ex. P.Pole, N.25 E., 68.56 feet, "BT", Ex. Maple 10", S.34 E., 82.42 feet, "BT", Ex. Maple 8", S.17 W., 73.51 feet, "BT", Ex. Maple 13", N.39 W., 178.39 feet, "BT". All existing references have a U.S.F.S. tag at breast height and a crown blaze scribed BT. All bearings are magnetic.

Signed by

Robert L. Jamros
25849

Date

12 April, 1995

Surveyor's Michigan License No.