

JAN 18 2001

For corners in

SECTION

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970

Approved by Alger County
Land Survey Remuneration
Peer Group Under Act 345 of
P.A. of 1990 On 12-13-2000

Donald W. Kinnunen
Chairman

05-213

Alger
(County)

Located in:

Corner Code #

- | | | | | | |
|---|---|-----|---|-----|-----|
| 1. Public Land Survey | T | 48N | R | 15W | I10 |
| | T | | R | | |
| | T | | R | | |
| | T | | R | | |
| 2. Property Controlling
in Section | S | T | R | | |
| | S | T | R | | |
| 3. Miscellaneous
Property in Section | S | T | R | | |
| | S | T | R | | |
| 4. Lot No. _____, Recorded Plat _____ | | | | | |
| 5. Private Claims _____ | | | | | |

FILED

TIME 8:50 AM

DEC 20 2000

DONALD W. KINNUNEN
REGISTER OF DEEDS
ALGER COUNTY, MI

Register of Deeds Stamp & File Number

I, Robert L. Jamros, in a field survey on September 27, 2000

do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

I10: PLS Geo. E. Adair, DS, 1851. Set quarter section post. W. Pine 15", N.77°W., 26 links. Maple 9", S.81°E., 31 links. ***** Michigan Department of Conservation, Forestry Division. Billy D. Buckler, RLS, 1956. Set 1" iron pipe with 4" brass cap from 1 original W. Pine BT, N.77°W., 26 links, in excellent condition. Blk. Spruce 9", N.45°E., 11 links. W. Birch 10", N.72°E., 57 links. Liber 2, Page 147, Alger County corner records. ***** No other subsequent restoration of record.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

I10: Found 1" iron pipe with 4" brass cap of 1956 report in good condition, NBT's and original BT have been removed in a recent clear cutting of this area, unable to identify. Existing monument as found is accepted as a careful and faithful perpetuation of the position of the original corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

I10: Existing 1" iron pipe with 4" brass cap as found. Established the following references with BT signs, blazed, scribed and painted. Set PK nails for measure with aluminum I.D. washers in the following: W. Pine 18", S.07°W., 89.35 feet (1/4S BT); Maple 5", S.56°E., 27.57 feet (1/4S BT); Maple 5", N.73°E., 22.60 feet (1/4S BT); W. Pine 14", N.38°E., 76.14 feet (1/4S BT). Survey marker sign on 6 foot steel post, N.45°W., 1.0 feet. All bearings are magnetic.

Signed by

Robert L. Jamros

Date

Dec 17, 2000

Surveyor's Michigan License No.

25849

