

REMONUMENTATION

APR 07 1998

ALLEGAN COUNTY REMONUMENTATION LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970.

SECTION
For corners in

Allegan (County)	Located in: Cheshire	Corner Code # D-13
1. Public Land Survey	T 1 N R 14W	S1/4 Sec 32
2.	T R	D-13
	T R	CHESHIRE
	T R	
2. Property Controlling in Section	S T R	
3. Miscellaneous Property in Sec.	S T R	

98 JAN 21 PM 1:18
REGISTER OF DEEDS
ALLEGAN COUNTY, MICH.

FILED

Register of Deeds Stamp & File
Number

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

I, Robert E. Lemke, in a field survey on April 20, 1997 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2													
3													
4													
5													
6													
7													
8													
9													
10													
11													
12													
13													

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:
D-13 GLO
40.00 Set qtr. section post
Sycamore 24 inch N 59 E 10 LINKS
Beech 24 inch N 38 W 46 LINKS
May 8th 1827
Wm. Brookfield
Witness card from Mitchell Surveys (1993)
Rebar
Power Pole NE 101.15'
NW Corner/Barn SE 98.0'
West sign post SSE 14.1'
CL E-W Road North 4' +/-
CL N-S Road South 9' +/-

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Found 5/8" diameter iron rod 0.55' below surface of gravel road. This iron fit all witnesses (power pole has only stump remaining). This iron measures west 2628.79' to C13 and measures east 2628.74' to E13 and is 0.06' north of a straight line drawn between C13 and E13.

And is accepted as a careful and faithful perpetuation of the position of the original corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Set standard Allegan County monument (3/4" x 24" steel rod w/red cap #23520) 0.6' below surface gravel road

Nail & Allegan Co. Remon Tag 1.3' above grade in west side of Power Pole N 30° E 93.35'
NW corner barn S 50° E 97.94'
W sign post S 20° E 14.16'
Nail & Allegan Co. Remon Tag 0.9' above grade in north side of Power Pole S 60° E 64.97'
Corner is 9' (+/-) west of Centerline 45th Street
Corner is 4' (+/-) south of Centerline Baseline Road

APPROVED REMONUMENTATION CORNER
P.A.345 OF 1990

ALLEGAN COUNTY

DATE APPROVED 6-10-97

COUNTY REP. K.V.O.

Date 12/31/97

Signed by Robert E. Lemke
For SDI CONSULTANTS, LTD

Surveyor's Michigan License No. 40160

FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS,

JAN. 28, 1971

REVISED MAY 14, 1975

REVISED JAN., 1983

REVISED OCT., 1995

USER 0006 PAGE 032