

APR 07 1998

ALLEGAN COUNTY REMONUMENTATION
LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

22

For corners in **SECTION**

Allegan (County) Located In: CHESHIRE Corner Code # HI-13(Seq. #1)

1. Public Land Survey	T 1 N R 14W	Cheshire
	T R	HI-13
	T R	(2008 #1)
	T R	
2. Property Controlling in Section	S 34 T 1 N R 14W	
	S T R	
3. Miscellaneous Property in Sec.	S T R	
	S T R	

98 JAN 21 PM 1:19
REGISTER OF DEEDS
ALLEGAN COUNTY, MICH.
Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

I, Robert E. Lemke, in a field survey on Dec. 11, 1997 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

A. Description of original monument and accessories and/or subsequent restoration:

Monument not set by G.L.O. This is a Allegan County witness monument.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

This point was set on the south line of Cheshire Township T1N, R14W, as established by H-13 & K-13. This position not established by original government surveyors. See Map on Back.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Set standard Allegan County witness monument (3/4" x 36" steel rod with w/ yellow Cap #23520).
Monument is 2038.00 feet East of H-1 on the town line.
Set Nail & Allegan Co. Remon Tag 1.1' above grade in SE side of 8" Elm N 25° E 11.88'
Set Nail & Allegan Co. Remon Tag 0.5' above grade in SE side of the west most 6"x6" post for sign S 65° W 8.98'
SW Corner of conc. boat launch ramp S 25° W 7.47'
Drill hole in concrete boat ramp S 43° E 2.60'
Water's edge of Eagle Lake is N 35° E 16.5 feet

APPROVED REMONUMENTATION CORNER
P.A.345 OF 1990
ALLEGAN COUNTY
DATE APPROVED 11-11-97
COUNTY REP. K.V.O.

Signed by Robert E. Lemke
For SDI CONSULTANTS, LTD
Surveyor's Michigan License No. 40160

Date 12/31/97

FORM APPROVED BY MICHIGAN STATE OF PROFESSIONAL SURVEYORS
JAN. 28, 1971
REVISED MAY 14, 1975
REVISED JAN., 1983
REVISED OCT., 1995

PAGE 1 OF 2

LINE 0006 PAGE 037