

APR 07 1998

ALLEGAN COUNTY REMONUMENTATION
LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

SECTION

For corners in

Allegan
(County)

Located In: Cheshire Corner Code # 1J-13(Seq. #2)

1. Public Land Survey

T 1 N R 14W ✓ 1J-13
T R CHESHIRE
T R (#2)
T R

2. Property Controlling
in Section

S 35 T 1 N R 14W

3. Miscellaneous
Property in Sec.

S T R
S T R

4. Lot No. , Recorded Plat

5. Private Claims

I, Robert E. Lemke, in a field survey on December 11, 1997 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5						3		2		1
3													
4	7		8		9				10		11		12
5													
6	18		17		16				15		14		13
7													
8	19		20		21				22		23		24
9													
10	30		29		28				27		26		25
11													
12	31		32		33				34		35		36
13													

A. Description of original monument and accessories and/or subsequent restoration:

Corner not set, by G.L.O., this is a Allegan County witness monument.

B. Description of corner evidence found and/or method applied in reestablishing Corner

This point was set on the south line of Cheshire Township, T.1 N., R.14 W., Allegan county. As established by H-13 & K-13 . This position not established by original government surveyors. See Map on Back.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Set standard Allegan County witness monument (3/4" x 36" steel rod with w/ yellow Cap #23520).
Set Nail & Allegan Co. Remon Tag 0.5' above grade in West side of a 4x6" Post in most northly end of fence N 47° E 25.61'
Set Nail & Allegan Co. Remon Tag 0.5' above grade in NW side of a 4x6" Post in most southerly end of fence S 5° E 56.98
Set Nail & Allegan Co Remon Tag 1.3' above grade in West side of a 30" Willow S75° E 51.47'
Set Nail & Allegan Co Remon Tag 0.7' above grade in North side of a 30" Willow S30° E 68.38'
Sequence corner is on Township line 30' South of edge of water.
Sequence corner is 3167.55' easterly from H-13

APPROVED REMONUMENTATION CORNER

P.A.345 OF 1990

ALLEGAN COUNTY

DATE APPROVED 11-11-97

COUNTY REP. K.V.O.

Signed by

Robert E. Lemke

For SDI CONSULTANTS,LTD.

Date 12-31-97

Surveyor's Michigan License No.40160

FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS.
JAN. 28, 1971
REVISED JAN., 1983
REVISED OCT., 1985

0006PAGE 039

PAGE 1 OF 2