APR 0.7 1998

## ALLEGAN COUNTY REMONUMENTATION LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

	. % 8
for corpers in a second of the	Faor
SECTION	ESS & AN
Allegan Located In: Cheshire Corner Code # IJ-13 (Seq. #3)	AN 21 PH
Public Land Survey T 1 N R 14W / TJ-13	現 の 翠 二
T R CHESHIRE T R CHESHIRE	
T R	· 85 —
2. Property Controlling S 35 T 1 N R 14W	· 9
in Section S T R	•
B. Miscellaneous S T R	Register of Deeds Stamp & File Number
Property in Sec. S T R	<u> </u>
•	
Lot No. , Recorded Plat	A B C D E F G H I J K L H
5. Private Claims	1
	2 5 4 3 2 2 1
Robert E. Lemke, in a field survey on April 20, 1997 do hereby state that under requirements of P.A. 74,	3
Aichigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and	4 3 - 8 9 10 11 12
ules therefore as required in the current manual of survey instructions of the United States Department of the atterior, Bureau of Land Management or by a decree of a Court of Law and for that the corner points mentioned in	5
ones 3. 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree	6 18 17 16 15 14 13
of a Court of Law; established, reestablished, monumented, recovered, found as expressed below:	7
	82021222324
NOTE: Not more than 2 corners, all in the same town and range, may be recorded	9
on this certificate.	10-30-29-2B-27-26-23-
	1
· ·	12-31-32-33-34-35-36-
and the state of t	13 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
A. Description of original monument and accessories and/or subsequent restoration:	
Monument not set by G.L.O. This is a Allegan County witness Monument.	
<ol> <li>Description of corner evidence found and/or method applied in restoring or reestablishing.</li> </ol>	an corner.
This point was set on the south line of Cheshire Township T.1 N., R.14 W., Allegan County	as established by H-13 & K-13.
This position not established by original government surveyors. See Map on Back.	
C. Description of monument for corner and accessories established to perpetuate locating the	he position of the corner:
2018 at 2018 at 2018 at 2018 at 2018 at 2018 and with and veillow Can	#22520)
Set standard Allegan County witness monument (3/4" x 36" steel rod with w/ yellow Cap Set nail & Allegan Co. Remon Tag 1.3' above grade in west side of a 58" Oak North 47.38	#25520j.
Set nail & Allegan Co. Remon Tag 1.2 above grade in SW side of a 8"Maple S 70°E 10.91	ft
and Iron Rad with cap LS#25867 South 0.77ft	
Set nail & Allegan Co. Remon Tag 1.6 'above grade in north side of 18" Hickory S 85°W 19 Set nail & Allegan Co. Remon Tag 1.3' above grade in SE side of a 8" Maple South 12.72ft	9.8011
Sequence corner is 4675,77 feet Easterly from H-13	
Nater's Edge of Eagle Lake is N70°E 67.50 feet	
	A DODONIED DESAONICISAENT ATIOM CODUCT
	APPROVED REMONUMENTATION CORNER P.A.345 OF 1990
	ALLEGAN COUNTY
	DATE APPROVED 11-11-97
	COUNTY REP. K.V.O.
	•
1 1	
Signed by Robert & Lamke	Date 12/31/97
For SDI CONSULTANTS,LTD.	
Surveyor's Michigan License No.40160	

PAGE 1 OF 2

USTR 0006 PAGE 041