

APR 07 1998

ALLEGAN COUNTY REMONUMENTATION
LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corner in SECTION

Allegan Located In: Cheshire Corner Code # JK-13(Seq. #4)

1. Public Land Survey T 1 N R 14W
T R
T R
T R
2. Property Controlling S 35 T 1 N R 14W
In Section S T R
3. Miscellaneous S T R
Property in Sec. S T R

JK-13
CHESHIRE
#4

98 JAN 21 PM 1:19
REGISTER OF DEEDS
ALLEGAN COUNTY
Jorge A. Brito

FILED

Register of Deeds Stamp & File Number

4. Lot No. Recorded Plat
5. Private Claims

I, Robert E. Lemke, in a field survey on December 11, 1997 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, reestablished, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5			4		3		2		1	
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

A. Description of original monument and accessories and/or subsequent restoration:

Corner not set. by G.L.O., this is an Allegan County witness monument.

B. Description of corner evidence found and/or method applied in reestablishing Corner:

This point was set on the south line of Cheshire township, T1N, R 14 W Allegan county. As established by H-13 & K-13. This position not established by original government surveyors. See Map on Back.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Set standard Allegan County witness monument (3/4" x 36" steel rod with w/ yellow Cap #23520).
Set Nail & Allegan Co. Remon Tag 7.5ft above grade in SE side of a 26" Poplar N 4° W 25.02ft
Set Nail & Allegan Co. Remon Tag 0.6ft above grade in East side of Power Pole #30\662 S 5° E 9.70ft
Set Nail & Allegan Co Remon Tag 2.1ft above grade in South side of a 84"Oak N88° E 29.71ft
Found Rebar with cap LS # 13583 GRD in centerline of road East 80.84ft
Sequence corner is 111ft East of Eagle Lake on Township line
Sequence corner is 6191.61ft Easterly from H-13.

APPROVED REMONUMENTATION CORNER
P.A.345 OF 1990
ALLEGAN COUNTY
DATE APPROVED 11-11-97
COUNTY-REP. K.V.O.

Signed by Robert E. Lemke

Date 12/31/97

For SDI CONSULTANTS,LTD.

Surveyor's Michigan License No.40160

FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS,
REVISED MAY 14, 1975
REVISED JAN., 1983
REVISED OCT., 1995

USER 0006 PAGE 043

PAGE 1 OF 2