

COMMISSION
For corners in
ALLEGAN
(County)

ALLEGAN COUNTY REMONUMENTATION
LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

	Located In:	Corner Code #
1. Public Land Survey	T 2N R 11W	I-6 (E 1/4, 15) MARTIN TWP.
	T R	
	T R	
	T R	
2. Property Controlling in Section	S T R	
	S T R	
3. Miscellaneous Property in Sec.	S T R	
	S T R	
4. Lot No. _____, Recorded Plat _____		
5. Private Claims _____		

1993 DEC 30 PM 2:42
Basil J. Address, Jr.
REGISTER OF DEEDS
ALLEGAN COUNTY, MICHIGAN

FILED

Register of Deeds Stamp & File Number

I, BASIL ADDRESS, in a field survey on DECEMBER 20, 1993,
do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned
in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the
current manual of survey instructions of the United States Department of the Interior, Bureau of Land
Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5
above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a
Court of Law; established, re-established, monumented, re-monumented, recovered, found as
expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

G.L.O. - NORTH BETWEEN SECTIONS 14 & 15, 40.00 CHS. SET 1/4 SECTION POST.
WITNESSES: BEECH 6 S 70 E 14 LKS. (9.24')
IRONWOOD 6 N 32 W 30 LKS. (19.80')
6-7-1877 J. W. HICKS, C.S. CALLS OUT STAKE & STONE FOR E 1/4 COR. SEC-15.
COUNTY SURVEYOR'S OLD NOTES: STAKE & STONE
WITNESSES: MAPLE 18 EAST 27'
MAPLE 16 NE 79'
MEAS. EAST 2653.5 TO CENTER
(CONTINUED ON BACK OF CERTIFICATE)

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:


FD. 1" IRON OVER STONE & BRICKS.
REPLACED 1" IRON WITH STD. ALLEGAN CO. MON.
THIS CORNER IS ACCEPTED AS A CAREFUL AND FAITHFUL PERPETUATION OF THE POSITION
OF THE ORIGINAL CORNER.

APPROVED BY THE ALLEGAN COUNTY REMONUMENTATION PEER GROUP 12-21-93.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

REPLACED 1" IRON W/ STD. ALLEGAN CO. MON. (3/4" STEEL PIN W/ REMON. CAP)
NAIL & REMON. WASHER N ROOT 36" MAPLE EAST 92.95'
NAIL & REMON. WASHER NW SDE 30" MAPLE N25 E 50.92'
1/2" IRON S 82 E 53.79'
1/2" IRON N 82 W 48.68'

(SKETCH ON BACK OF CERTIFICATE)



Signed by Basil Address, Jr.
Surveyor's Michigan License No. 30075

Date 12-29-93

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, 1971
REVISED MAY 14, 1975
REVISED JAN., 1983

LIBER 004 PAGE 294

SHEET 1 OF 2

(CONTINUED FROM FRONT OF CERTIFICATE)

A. DESCRIPTION OF ORIGINAL MONUMENT AND ACCESSORIES AND/ OR SUBSEQUENT RESTORATION.

7-30-68- D. A. RATEKIN, C.S. FD. STONE & BRICKS RAISED WITH 1" SOLID IRON.

WITNESSES: MAPLE 28" EAST 27.4'
 MAPLE 24" NE 78.5'
 STEEL FE POST WEST 22.7'
 MAPLE 36" EAST 91.3'
 MEAS. SOUTH 2642.55' TO SEC. COR.

1971 - D. A. RATEKIN, C.S. L.C.R.C. (L-1, P-100)

1993 - WIGHTMAN MOORED MEAS. SOUTH 2643.48' TO SEC. COR.
 MEAS. NORTH 2647.81' TO SEC. COR.

