

RECEIVED  
MAR 07 2000

FILED

ALLEGAN COUNTY REMONUMENTATION

LAND CORNER RECORDATION CERTIFICATE 00 FEB -1 AM 8:37

Filing Requirement of Act 74, Mich. P.A. 1970

SECTION

For corners in

Allegan  
(County)

Located In:

Corner Code #

1. Public Land Survey

T2N R15W

A-6

T R

T R

T R

West 1/4 corner

Section 18

Clyde Twp.

2. Property Controlling  
in Section

S T R

S T R

3. Miscellaneous

S T R

Property in Sec.

S T R

4. Lot No. , Recorded Plat

5. Private Claims

I, Steve Lampen, in a field survey on December 22, 1999, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

A-6

Corner not monumented by GLO Survey.

No other records recovered

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

A-6 No corner monumentation found. Re-established corner mid-way between A-5 and A-7 and on line between M-6 and M-7, T2N, R16W. Corner is in a North and South drain with no East and West occupation.

See sketch on back

Set an Allegan County Remonumentation iron and cap at the corner. Corner not monumented by the original GLO Survey. This monument is accepted as the best available evidence of the position of the corner. Approved by the Allegan County Remonumentation Peer Group on December 28, 1999.

APPROVED REMONUMENTATION CORNER

P.A. 345 OF 1990

ALLEGAN COUNTY

DATE APPROVED DEC. 28, 1999

COUNTY REP. [Signature]

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

A-6 Allegan County Remonumentation iron and cap.

Azimuth = Michigan State Plane grid direction

Centerline North and South drain	270°	3'
10" Pine, remonumentation tag in W side	156° 53'	62.80'
1/2" diameter steel bar with cap #37279	318° 53'	55.34'
1/2" diameter steel bar with cap #37279	234° 35'	32.20'
1/2" diameter steel bar with cap #37279	26° 24'	48.65'
M-6, T2N, R16W	359° 26'	33.00'

Signed by Steven Lampen

Date DECEMBER 31, 1999

Surveyor's Michigan License No. 37279

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, 1971  
REVISED MAY 14, 1975  
REVISED JAN., 1983  
ADAPTED FOR WORD PROCESSING MARCH, 1993

MAR 67 2000

SECTION

LIBR0007 PAGE 183

