

RE

FILED

MAR 07 2000

**ALLEGAN COUNTY REMONUMENTATION  
LAND CORNER RECORDATION CERTIFICATE**  
Filing Requirement of Act 74, Mich. P.A. 1970

00 FEB -1 AM 8:38

**SECTION**

For corners in

Allegan

(County)

Located In:

Corner Code #

1. Public Land Survey

T2N R15W

BC-11, Sequence

T R

No. 3

T R

Section 31

T R

Clyde Twp.

2. Property Controlling  
in Section

S T R

S T R

3. Miscellaneous

S T R

Property in Sec.

S T R

4. Lot No. \_\_\_\_\_, Recorded Plat \_\_\_\_\_

5. Private Claims \_\_\_\_\_

Register of Deeds Stamp &amp; File Number

I, Steve Lampen, in a field survey on \_\_\_\_\_ 19\_\_\_\_\_, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

**NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.**

A. Description of original monument and accessories and/or subsequent restoration:

C-11

GLO - Britain -1831

Set post

Birch 10 S 67 E 12

Jam 18 N 82 W 13

Ratekin - iron at intersection of ditches

Mitchell Surveys - iron at intersection of ditches

C-11 to C-9 = 5278.55

C-11 to E-11 = 5281.60

C-11 to B-11 = 2647.18

C-11 to C-12 = 2643.38

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

C-11 Did not find iron. Re-established C-11 by intersecting the record distances of C-11 to C-9 = 5278.55 and C-11 to E-11 = 5281.6. This location gives C-11 to C-12 record 2643.38 vs. meas. 2642.06' and C-11 to B-11 record = 2647.18 vs. meas. 2646.24. See sketch on back.

Corner falls in intersection of drains to North, South and East. Set an Allegan County remonumentation iron and cap 25.0' West of C-11 on line between C-11 and B-11.

Accepted the location of C-11 as a careful and faithful perpetuation of the position of the original corner.

Approved by the Allegan County Remonumentation Peer Group on December 28, 1999.

Traversed 15,848' off road.

APPROVED REMONUMENTATION CORNER

P.A. 345 OF 1990

ALLEGAN COUNTY

DATE APPROVED DEC. 28, 1999

COUNTY REP. *Mike J. Donohue*

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

BC-11, Sequence No. 3 Allegan County Remonumentation iron and yellow cap 25.0' West of C-11 on line between C-11 and B-11

Azimuth = Michigan State Plane grid direction

Centerline North end 24" concrete culvert 32° 36.03'

Centerline South end 24" concrete culvert 152° 46.28'

1/2" diameter steel bar with cap #37279 222° 36' 55.09'

1/2" diameter steel bar with cap #37279 312° 43' 72.33'

Signed by *Steven Lampen*Date DECEMBER 31, 1999

Surveyor's Michigan License No. 37279

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, 1971  
REVISED MAY 14, 1975  
REVISED JAN., 1983  
ADAPTED FOR WORD PROCESSING MARCH, 1993

MAR 07 2000

SECTION

31 648

59TH STREET

STREET

Bravo

BM 661

113TH

MEAS. = 2642.06  
REC. = 2643.38

179°30'17"

MEAS. = 2646.24  
REC. = 2647.18

270°49'40"  
C-11  
SET REMON 15' W.

MEAS. 5281.6  
REC. + 5281.6

271°05'08"

REC. + 5278.55  
MEAS.

358°28'56"

2639.275

C-10  
SET REMON

358°28'56"

2639.275

SE COR. → NW COR.  
REC. + MEAS.  
92°34'43"

358°44'25"  
2629.48

358°36'25"  
2632.88

Sandpits

AND

116TH AVE

REC. + MEAS. 5299.92  
271°15'08"

C-9  
SET REMON

359°14'47"

2638.44

58TH

640

STREET

359°14'32"

2638.17

633

118TH

STREET

BM 657

Pearl

Townhall

OHIO

20

9

AVENUE

C L