

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A. 1970

FOR CORNERS OF --	LOCATED IN --	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY SEC. 4 T. 2 S. R. 15 W.		G-1, E-1
2. PROPERTY CONTROL- ING IN SECTION T. S. R. E.		
3. MISCELLANEOUS PROPERTY IN SECTION T. S. R. E.		
4. LOT NO. , RECORDED PLAT		
5. PRIVATE CLAIMS		

RECORDED
MAR 1 11 40 AM 1974
REGISTER OF DEEDS
MICHIGAN

REGISTER OF DEEDS STAMP AND
FILING NUMBER

I, DENNIS A. MIDDLETON, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above (identified with circles on index code diagram - over) were, in a field survey on FEBRUARY 11, 1974, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on 19, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

G-1. B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:
THIS CORNER WAS ESTABLISHED AT THE GOVERNMENT JOG DISTANCE FROM THE SOUTHEAST CORNER OF SECTION 33, AS RECORDED BY DON R. RATEKIN, SET ON TOWN LINE.

G-1. C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:
NORTHWEST CORNER E-1, NORTHWEST CORNER
RAILROAD SPIKE WITH X CUT IN IT FOUND 1-1/4" IRON BAR
SPIKE IS IN E EAST AND WEST ROAD IN CENTERLINE EAST AND WEST ROAD
SPIKE IS 51' WEST OF E. ROAD TO SOUTH UTILITY POLE N. 70° E. 65.58' TO NAIL
POWER POLE S. 30° E. 73.51' TO NAIL, 9' HIGH UTILITY POLE S. 65° E. 36.78' TO NAIL ON FACE
POWER POLE N. 40° W. 57.69' TO NAIL, 8' HIGH CORNER IS ON EAST LINE OF DRIVE TO SOUTH
POWER POLE N. 35° E. 81.36' TO NAIL, 8' HIGH

SIGNED BY Dennis A. Middleton DATE 2/22/74
SMITH AND SMITH, INC.
SURVEYOR'S MICHIGAN REGISTRATION NO. 16049 (SEAL)
FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____
CHIEF OF SURVEY PARTY
APPROVED AND SIGNED BY _____ DATE _____
MICHIGAN REGISTERED LAND SURVEYOR (SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. _____

Form No. MLM 736
DOUBLE DAY BROS. & CO., KALAMAZOO, MICH.

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971
DISTRIBUTED BY MICHIGAN SOCIETY OF REGISTERED LAND SURVEYORS

2 PAGE 273