

APR 07 1998

SECTION

Allegan County Remonumentation
LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970For corners in
Allegan

(County)

Located In:

Corner Code #

1. Public Land Survey

T 3N R 12W

D-1 (N1, 5)

T R

Hopkins Twp.

T R

2. Property Controlling
in Section

S T R

S T R

3. Miscellaneous
Property in Sec.

S T R

S T R

4. Lot No. Recorded Plat

5. Private Claims

98 JAN 21 PM 1:24
REGISTER OF DEEDS
ALLEGAN COUNTY, MICH.

FILED

Register of Deeds Stamp & File Number

I, John C. Bueche, in a field survey on October 4, 19 96
do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned
in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the
current manual of survey instructions of the United States Department of the Interior, Bureau of Land
Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5
above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a
Court of Law; established, re-established, monumented, re-monumented, recovered, found as
expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

D-1 GLO Old notes, 1876 Card
Not set 39.96' E & W No inform.
Beech 12 NE 80
Sandfur 4 SW 33

Jonker, 1984
S 1/4 32, 2-12
Notes pointed East 6.6'

APPROVED REMONUMENTATION CORNER
P.A. 345 OF 1990
ALLEGAN COUNTY
DATE APPROVED 5-13-97
COUNTY REP. K.V.O.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

D-1 Found stone on South line of Twp. 6.6' East of S 1/4 cor. Sec. 32,
4-12
Meas. West (S 1/4 32, 4-12 2649.12 + 6.6) (Jonker 2648.63 + 6.6)
Meas. East (S 1/4 32, 4-12 2657.46 - 6.6) (Jonker 2657.44 - 6.6)

This position not established by original government surveyors.
This monument is accepted as the best available evidence of the
position of the corner.

Peer group approved May 13, 1997.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:
D-1 Replaced stone with Allegan Co. Mon. (3/4" x .36" Pin with Cap)
left stones

Nail & Allegan Co. Remon. Tag in N side 8" Oak N 48° W 72.67'
Nail & Allegan Co. Remon. Tag in E side 10" Sassafras S 0° E 46.95'
Nail & Allegan Co. Remon. Tag in W side 20" Oak N 24° W 79.49'
Nail & Allegan Co. Remon. Tag in S side 12" Ash N 10° E 96.09'
Spk. in S side PP N 85° W 154.78'
Allegan Co. Mon. S 1/4 32, 4-12 East 6.6'

Signed by John C. Bueche, P.S.

Surveyor's Michigan License No. 13027

Date

5-29-97

LSE 0006 PAGE 128

