APR 2 5 1995

## COMMISSION

ALLEGAN COUNTY REMONIMENTATION LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

ク 2番号	Ŕ	<b>4</b> 66	
(1071) (1031)	200	230	T
EGISTER OF L	1	9	
F DE LOS SOLDA	6	AH 9: 5	· M
Sis	2	جې	U
~	£3;	C)	

For corners in

ALLEGAN Located In: 1. Public Land Survey T-3N R-13W SW SEC-3 R Monterey Two. R 2. Property Controlling R in Section Miscellaneous S

Register of Deeds Stamp & File Number

Property in Sec.

4. Lot No. 5. Private Claims

I BASIL ANDRESS in a field survey on 29 JIM 1994 do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior. Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

GLO: NORTH BETWEEN SECTIONS 9 & 10 80.00 SET POST CORNER SECTIONS 3,4,9 & 10 BEECH 19 N 7 E 9 LKS. BEECH 6 S 29 W 29LKS.

D.A. RATEKIN, C.S. 1967-FD. 1" IRON IN MON. BOX, DIST. EAST TO 1/4 COR 2672.17: 1973-L.C.R.C. L-2, P-181

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

FD. 1" IRON IN MON. BOX DIST. EAST TO 1/4 COR 2672.26 CHECKED WITH REMAINING WITNESSES FROM L.C.R.C. -PP SSW 83.8' -18" MAPLE NW 42.0

APPROVED REMONUMENTATION CORNER P.A. 343 OF 1990
ALLEGAN COUNTY
DATE APPROVED 7-12-94
COUNTY REP. MARKET

THIS CORNER IS ACCEPTED AS A CAREFUL AND FAITHFUL PERPETUATION OF THE POSITION OF THE ORIGINAL CORNER.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner PLACED AN ALLEGAN COUNTY REMON. CAP OVER IRON IN MON. BOX OF MICA

16d & REMON. TAG SE SDE PP S 25 W 84.00'
16d & REMON.TTAGENESSDE:18" MAPLE NU55:W 142113' 16d & REMON. TAG NE SDE 26" HICKORY N 30 W 112.93 16d & REMON. TAG SW SDE 12" WALNUT N 15 W 328.37 SW COR HSE #3408 N 80 W 146.91'
NE COR GARAGE N 45 W 128.27'

anorese, JR. PROFESSIONAL SURVEYOR NO.

BASIL

Date 20 AUG 94

FORM APPROVED BY MICHIGAN STATE HOARD OF LAND SURVEYORS, JAM. 28, 1971 REVISED MAY 11, 1975 APPLIED JAM., 1985

<u>ે છાવ0005માંદ્ર</u>032