

APR 07 1998

ALLEGAN COUNTY REMONUMENTATION
LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

SECTION
For corners in

ALLEGAN
(County)

Located in:

Corner Code #

1. Public Land Survey

T R
T R
T R
T R

✓ E 12-13
Monterey Twp
#2

2. Property Controlling
in Section

S-32 T-3N R-13W
S-33 T-3N R-13W

MONTEREY TWP
MONTEREY TWP

3. Miscellaneous
Property in Sec.

S T R
S T R

4. Lot No. Recorded Plat

5. Private Claims

I, Arthur W. Brintnall, in a field survey on 17 OCT 19 97 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

G.L.O.

WEST ON S SIDE SEC 33
80.00 CORNER SECS 32 & 33 IN LAKE
NO BEARINGS

AUG 29, 1869 J.W. HICKS, C.S.

MEANDER POST 2005.74 FT 30.39 CHS S OF E 1/4 COR
SURVEYED EAST 30 ACRES OF SE FRAC 1/4 SEC-32, T-3N, R-13W

MAR 21, 1994 K.L. VAN ORDER, C.S.

SURVEY N OF AND ADJOINING BISHOP'S PLAT NO. 2
WHICH ADJOINS W. LINE OF E 30-ACRES
SURVEYED BY HICKS

APPROVED REMONUMENTATION CORNER
P.A. 345 OF 1990
ALLEGAN COUNTY

DATE APPROVED 10-14-97
COUNTY REP. K.V.O.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

SEE SKETCH ON BACK OF CERTIFICATE

SET STD ALLEGAN CO. MON. (3/4"x36" IRON W/CAP) ON SEC LINE AS ESTABLISHED BY K.L. VAN ORDER, C.S. ON SURVEY DATED 21 MAR 94.

THIS POSITION NOT ESTABLISHED BY G.L.O. THIS MONUMENT IS ACCEPTED AS THE BEST AVAILABLE EVIDENCE OF THE POSITION OF THE CORNER.

APPROVED BY ALLEGAN CO. PEER GROUP 14 OCT 97

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

STD ALLEGAN CO. MON (3/4"x36" IRON W/CAP)

- E-12 NORTH 1871.00 FT
- NE COR 11.5'X17' CONC BLK BLDG SOUTH 37.36'
- NW COR 11.5'X17' CONC BLK BLDG S 25°W 41.94'
- 16D & REMON TAG E SIDE 18" ELM S15°E 13.04'
- 16D & REMON TAG N SIDE 18" APPLE N60°E 34.52'
- 16D & REMON TAG W SIDE 16" & 20" CHERRY N15°W 23.53'
- DUMONT LAKE SOUTH 226'±

Signed by Arthur W. Brintnall

Date OCT, 29, 1997

PREIN & NEWHOF

Surveyor's Michigan License No. #28407

LIBER 0006 PAGE 167

SHEET 1 OF 2

FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 23, 1971
REVISED MAY 14, 1975
REVISED JAN., 1983
REVISED OCT., 1995

98 JAN 21 PM 1:26
Jorge A. C. C. C.
REGISTER OF DEEDS
ALLEGAN COUNTY MICH.

FILED

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	5	5											
3													
4	7	8											
5													
6	10	17											
7													
8	19	20											
9													
10	30	29											
11													
12	31	32											
13													

