

**ALLEGAN COUNTY REMONUMENTATION  
LAND CORNER RECORDATION CERTIFICATE**  
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Allegan  
(County)

Located In:

Corner Code #

*Other #2*

1. Public Land Survey

T    R    F 1-2  
T    R    Heath Twp.  
T    R    (See #2)  
T    R   

2. Property Controlling  
in Section

S 4 T 3N R 14W Heath Twp.

3. Miscellaneous  
Property in Sec.

S    T    R     
S    T    R   

97 JAN 22 11:23  
REGISTERED  
ALLEGAN COUNTY

FILED

Register of Deeds Stamp & File Number

4. Lot No.         , Recorded Plat           
5. Private Claims         

I, Kirk L. Van Order, in a field survey on Nov. 11, 1996 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and for that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law, established, re-established, monumented, recovered, found as expressed below.

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5			4		3		2		1	
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

A. Description of original monument and accessories and/or subsequent restoration:

APPROVED REMONUMENTATION CORNER

P.A. 345 OF 1990

ALLEGAN COUNTY

DATE APPROVED 11-26-96

COUNTY REP. Kirk L. Van Order

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Set standard Allegan County witness monument on North & South 1/4 line of Section 4 on higher lowland on South bank of swamp  
AZ 180°16'03" 670.80 feet from F-1 computed position and  
AZ 00°16'03" 5441.95' from F-3. (SEE OTHER SIDE FOR SKETCH)

This position not established by original government surveyors.  
This monument is accepted as the best available evidence of the location of the corner.  
group approved Nov. 26, 1996.  
versed distance 8064.5 feet offroad.

C. Descr: monument for corner and accessories established to perpetuate locating the position of the corner:


Set standard Allegan County witness monument (3/4" x 36" steel rod w/yellow cap #23520)  
SE corner concrete slab AZ 214°37'20" 35.60'  
SE corner 2-story building AZ 293°34'40" 34.21'  
NE corner 2-story building AZ 285°23'03" 18.30'  
NE corner concrete slab AZ 286°07'22" 14.40'  
Nail & Remon. tag in N side power pole AZ 109°06'35" 71.32'  
Top of slope AZ 00°00'00" 9'+

Signed by

Surveyor's Michigan License No. 23520

Date

12-31-96



FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 29, 1971  
REVISED 10/24/1975  
REVISED 10/14, 1983  
REVISED OCT., 1986

0005 PAGE 401

PAGE 1 OF 2

F 1-2 HEATH TWP.

