

**ALLEGAN COUNTY REMONUMENTATION
LAND CORNER RECORDATION CERTIFICATE**
Filing Requirement of Act 74, Mich. P.A. 1970

LIBR0006 PAGE 05

For corners in

Allegan
(County)

Located in:

Corner Code #

FILED

1/28/1999 2:44:39 PM

JOYCE A. WATTS
REGISTER OF DEEDS
ALLEGAN COUNTY, MICH

1. Public Land Survey

T___ R___ D 1-2
T___ R___ Heath Twp. (Seq. #12)

2. Property Controlling
in Section

S 5 T 3N R 14W

3. Miscellaneous
Property in Sec.

S___ T___ R___

S___ T___ R___

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____

5. Private Claims _____

I, Kirk L. Van Order, in a field survey on Dec. 23, 1998 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law, established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

1	A	B	C	D	E	F	G	H	I	J	K	L	M
2				5		4		3		2		1	
3													
4													
5													
6													
7													
8													
9													
10													
11													
12													
13													

A. Description of original monument and accessories and/or subsequent restoration:

D-1 Falls in Bayou

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Set standard Allegan Co. reference monument on line between D-1 computed position and D-2 said reference monument being S.01°-04'-46" W. 788.93' from D-1 and N. 01°-04'-46" E. 2133.85' from D-2. This position not established by original government surveyors. This monument is accepted as the best available evidence of the position of the corner.
Peer group approved Dec. 22, 1998.

APPROVED REMONUMENTATION CORNER
P.A. 345 OF 1990
ALLEGAN COUNTY
DATE APPROVED DEC. 22, 1998
COUNTY REP. Kirk L. Van Order

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Set standard Allegan Co. Remon. reference monument (3/4" x 36" steel rod w/yellow cap inscribed Remon. Ref. Pt. #23520)
Nail & Remon. tag in NE side 13" maple AZ 125° 3.38'
Nail & Remon. tag in NW side 24" ash AZ 225° 12.36'
Nail & Remon. tag in NE side 19" ash AZ 310° 15.83'
NW corner conc. dam 23.63'
SW corner conc. dam 20.73'
North edge of Rabbit River AZ 180° 119'+/-
South edge of Bayou AZ 00° 56'+/-

Signed by Kirk L. Van Order
Surveyor's Michigan Professional No. 23520

Date 1-13-99



