

00000001

SECTION

ALLEGAN COUNTY REMONUMENTATION
LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Allegan

(County)

Located In:

Corner Code #

1. Public Land Survey

T3N R16W

M-12

T R

T R

T R

E 1/4 Corner

Section 36

Saugatuck Twp.

2. Property Controlling
in Section

S

T R

S

T R

3. Miscellaneous
Property in Sec.

S

T R

S

T R

4. Lot No. , Recorded Plat

5. Private Claims

I, Steve Lampen, in a field survey on December 4, 1999, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

M-12
1831 - L. Lyon - Set Post
Pine 7 N42W 10
Tamarak 7 S32W 29

Old county surveyors notes show
M-11 to M-12 = 2640.8
M-12 to M-13 = 2640.8

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

M-12
No corner found.

Set standard Allegan County Remon 1/4" x 36" iron with red cap #23520 equidistant and on line with M-11 and M-13. See sketch on back.

Traversed off Road 5280 feet.

Approved by the Allegan County Remon Peer Group on December 14, 1999, and is accepted as a careful and faithful re-establishment of the position of the original corner.

APPROVED REMONUMENTATION CORNER

P.A. 345 OF 1990

ALLEGAN COUNTY

DATE APPROVED DEC. 14, 1999

COUNTY REP. [Signature]

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

M-12 Standard Allegan County Remonumentation 1/4" x 36" iron with red cap #23520.
Azimuth = Michigan State Plane grid direction.

Remonumentation tag in N side 24" Pine	280° 50'	381.69'
Remonumentation tag in S side 24" Maple	273° 12'	368.30'
Remonumentation tag in W side 24" Maple	157° 44'	496.82'
Remonumentation tag in NW side 6" Ash	230° 50'	143.22'
C1 Ditch towards the East	180° 0'	7'
A-12, T3N, R15W	180° 14'	4.29'

Signed by Steven Lampen

Date DECEMBER 31, 1999

Surveyor's Michigan License No. 37279



RECORD 242
SECTION 31

MAR 07 2000

SECTION

M A

SECTION 36
T3N R16W

SECTION 31
T3N R15W

11

GLO + MEAS
8.58

N 0° 14' 03" E

2639.77

2635.48

12

N 0° 14' 03" E

2639.77

2635.48

13

LIBERO 007, PAGE 1, 37