

SURVEY &  
REMONUMENTATION

APR 25 1995

COMMISSION

For corners in

Allegan  
(County)

Located in:  
Dorr Twp.

Corner Code #

1. Public Land Survey

T 4N R 12W

A-1

2. Property Controlling  
in Section

S T R

3. Miscellaneous  
Property in Sec.

S T R

4. Lot No. , Recorded Plat

5. Private Claims

Allegan County Remonumentation  
LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970

1994 DEC 16 AM 9:56  
REGISTER OF DEEDS  
ALLEGAN COUNTY MICHIGAN  
*Robert J. Jonker*

FILED

Register of Deeds Stamp & File Number

I, Robert Jonker, in a field survey on August 06, 1994,  
do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned  
in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the  
current manual of survey instructions of the United States Department of the Interior, Bureau of Land  
Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5  
above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a  
Court of Law; established, re-established, monumented, re-monumented, recovered, found as  
expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded  
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

G.L.O. survey, 1826 No info. of value from any old Corner common to 4 Twp.  
Beech 10", S 71° E 41' County Surveyors notes or from  
Beech 13", N 22° E 28' the Road Commission.

C.P. Co. wit. 1976, Pd. "T" Iron L.C.R.C., Liber 3, Pg. 267.  
SW cor. h/w N 30° W 34.8' Nederveld & Jonker, 1979 (OVER)  
SE cor. h/s N 30° E 33.25' "T" Iron per C.P. Co. wit.  
W. end metal Culv. S 30° W 37.07' PK in SE side P.pole NE 62.55'  
PK in W. side P.pole SSE 79.20'  
Nail W. side 12" Walnut NNE 43.70'

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Found 4" dia. cast iron monument (Harrison) mon. set by Kent Co. at the  
corner of Byron Twp.  
Per L.C.R.C., Liber 3, Page 267  
PK W. side P.pole SSE 79.20'  
Nail W. side 12" Walnut NNE 43.70'

APPROVED REMONUMENTATION CORNER  
P.A. 345 OF 1990  
ALLEGAN COUNTY  
DATE APPROVED 8-9-94  
COUNTY REP. *Robert J. Jonker*

C. Description of monument for corner and accessories established to perpetuate locating the position of

4" Cast Iron Harrison Monument

Allegan Co. N&T W. side 16" Walnut Az. 30° 43.62'  
Allegan Co. N&T N. side G.pole Az. 65° 62.45'  
PK Nail W. side P.pole Az. 155° 79.36'  
C/L E-W pavement is South 3'±  
on C/L N-S gravel



Accepted as a careful and faithful perpetuation of the position of the  
original corner.

Signed by Robert J. Jonker  
JONKER LAND SURVEYS  
Surveyor's Michigan License No. 21572

Date August 09, 1994

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 26, 1971  
REVISED MAY 14, 1975  
REVISED JAN., 1983

USE 0005 PAGE 077

Sheet 1 of 2

Allegm

A-13, T5N, R12W  
Recorded by LCRC's #37, 1509, 4634

LCRC #37, W & W, 1971, looked for stone, did not find, found spk. 2' down  
@ C/L "X", accepted, set "T" iron

LCRC #1509, W & W, 1980  
Found "T" iron, set K.C. monument

LCRC #4634, Bueche, 1988  
Remon. maint.