

MAR 16 1994

Allegan County Remonumentation
LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in
Allegan
(County)

Located In:

Corner Code #

1. Public Land Survey

T 4N R 13W

D-13 (S 1/4, 32)

T R Salem Twp.T R 2. Property Controlling
in SectionS T R S T R

3. Miscellaneous

S T R

Property in Sec.

S T R 4. Lot No. , Recorded Plat 5. Private Claims

Register of Deeds Stamp & File Number

I, John C. Bueche, in a field survey on October 26, 19 93,
do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned
in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the
current manual of survey instructions of the United States Department of the Interior, Bureau of Land
Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5
above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a
Court of Law; established, re-established, monumented, re-monumented, recovered, found as
expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded
on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
2													
3													
4													
5													
6													
7													
8													
9													
10													
11													
12													
13													

A. Description of original monument and accessories and/or subsequent restoration:

D-13 1/2" iron, no date
16" Ash SE PK E side 55.15'
9" Hickory NNW PK E side 50.72'
Quad. Oak 7, 8, 9, 10" NE
PK SE side 10" 36.41'
2649.39' E to SW 32
2649.39' E to SE 32
49.88' W to N 1/4 3, 13

1/2" rod, LCRC L2, P93, 5-8-73
5-8-73 set 1/2 way between sec. cor.
NE 75.16' clump of trees
SE 82.80' 36" Maple
NW 54.83' Tr. Sycamore
SE 54.62' 15" Ash

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

D-13 Found capped rerod REM #26463, down 6"
9" Hickory NNW PK E side 50.72'
Quad. Oak 7, 8, 9, 10" NE PK SE side 10" 36.41'
Meas. W SW 32, 2649.40'
Meas. W N 1/4 5, 3-13
49.95' on line between S 1/4 & SE 32, 4-13

And is accepted as a careful and faithful perpetuation of the
position of the original corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

D-13 Replaced rerod with Std. Allegan Co. Mon. (3/4" x 24" Pin & Cap)
Conc. Nail & Allegan Co. Remon. Tag in E side 10" Hickory N 20° W 50.42'
Conc. Nail & Allegan Co. Remon. Tag in SE side 10" Oak N 35° E 36.59'
Conc. Nail & Allegan Co. Remon. Tag in E side 16" Oak S 60° W 91.37'
(4.5' high)
Conc. Nail & Allegan Co. Remon. Tag in E side 20" Oak S 30° W 54.97'
C/L two track S, W 37'±
On C/L gravel road E-W
Meas. by hand

Signed by

John C. Bueche

Date

Oct 26, 1993

Surveyor's Michigan License No.

13027

FORM APPROVED BY MICHIGAN STATE BOARD OF SURVEYORS, JAN. 28, 1971
REVISED MAY 14, 1973
REVISED JAN., 1983

LIBER 004 PAGE 234