

SURVEY &
REMONUMENTATION

APR 24 1995

COMMISSION

For corners in

ALLEGAN COUNTY REMONUMENTATION

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970

Allegan (County)

Located In:

Corner Code #

1. Public Land Survey

T 4N. R 14W.

E-8 (E 1/4 - Sec. 20)

T R

Overisel-Twp.

T R

T R

2. Property Controlling
in Section

S T R

S T R

3. Miscellaneous
Property in Sec.

S T R

S T R

4. Lot No. , Recorded Plat

5. Private Claims

I, Gerald T. Ford, in a field survey on November 17, 19 93, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

E-8

1831

Government Land Office Survey Notes

Post

20" Beech

N16°E

5 links

24" Beech

S30°W

33 links

E-8

Consumers Power Co. Witnesses (Drawing No SF 16897)

Iron

Street Sign

SE

21.6'

SW Cor Headwall

NW

41.8'

SE Cor Headwall

NE

40.8'

Fence Post

SE

32.25'

Center, Sec. 20 T4N R16W

W

2648.69'

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

E-8

Found 1/2" steel bar and accepted in as a careful and faithful perpetuation of the position of the original corner.

Found PK NE Face 12" Nut Tree

ESE

55.84'

Found PK NW Face 18" Ash Tree

SW

50.46'

Center Sec 20 T4N, R16W

W

2648.98'

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

E-8

Replaced 1/2" steel bar with A.C. Remonumentation Iron & Cap

A.C. Remon tag & nail in E face 24" Ash

AZ.

202° 50.28'

A.C. Remon tag & nail in W face 16" Walnut

AZ.

152° 68.48'

A.C. Remon tag & nail in N face 10" Elm

AZ.

125° 38.52'

A.C. Remon tag & nail in N face 16" Walnut

AZ.

108° 55.78'

Set "X" cut in top of E end 24" CMP culvert

AZ.


18° 42.97'

N-S Tree row to South

AZ.

270° 17' ±

APPROVED REMONUMENTATION CORNER
P.A. 345 OF 1990
ALLEGAN COUNTY
DATE APPROVED 12-14-93
COUNTY REP. [Signature]



Signed by

Gerald T. Ford

Date

January 21, 1994

Surveyor's Michigan License No. 33976

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 24, 1971
REVISED MAY 14, 1973
REVISED JAN., 1983

W:\Dect\Surr\Remon.doc

LIBER

004 PAGE 382