

ALLEGAN COUNTY REMONUMENTATION  
LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Allegan  
(County)

Located In:

Corner Code #

*Other #2*

1. Public Land Survey

T\_\_\_ R\_\_\_  
T\_\_\_ R\_\_\_  
T\_\_\_ R\_\_\_  
T\_\_\_ R\_\_\_

F 12-13 Overisel

2. Property Controlling  
in Section

S 33 T 4N R 14W  
S\_\_\_ T\_\_\_ R\_\_\_  
S\_\_\_ T\_\_\_ R\_\_\_  
S\_\_\_ T\_\_\_ R\_\_\_

Overisel Twp.

3. Miscellaneous  
Property in Sec.

4. Lot No. \_\_\_\_\_, Recorded Plat \_\_\_\_\_

5. Private Claims \_\_\_\_\_

I, Kirk L. Van Order, in a field survey on Nov. 21, 1996 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6	5	4	3	2	1							
3													
4	7	8	9	10	11	12							
5													
6	18	17	16	15	14	13							
7													
8	19	20	21	22	23	24							
9													
10	30	29	28	27	26	25							
11													
12	31	32	33	34	35	36							
13													

A. Description of original monument and accessories and/or subsequent restoration:

APPROVED REMONUMENTATION CORNER

P.A. 345 OF 1990

ALLEGAN COUNTY

DATE APPROVED 11-26-96

COUNTY REP. Kirk L. Van Order

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Set standard Allegan County witness monument on the North and South 1/4 line of Sec. 33 as established by a straight line extension from F-11 thru F-12 to a point on top of the North bank of a swamp. Said point being AZ 359°08'23" 834.51 feet from computed position F-13. Also being AZ 179°08'23" 1836.38 feet from F-12. (off road traverse)

This position not established by original government surveyors. This monument is accepted as the best available evidence of the position of the corner.  
Peer group approved.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Set standard Allegan County witness monument (3/4" x 36" steel rod w/yellow cap #23520)

Nail & Remon. tag in N side 20" Cherry	AZ 95°	32.79'
Nail & Remon. tag in W side 10" Cherry	AZ 180°	14.48'
Nail & Remon. tag in NW side 14" Cherry	AZ 210°	30.04'
Nail & Remon. tag in SE side 10" Cherry	AZ 230°	33.05'
Top of slope	AZ 180°	14.5'

Signed by Kirk L. Van Order

Date 12-31-96

Surveyor's Michigan License No. 23520



FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 22, 1971  
REVISED MAY 14, 1975  
REVISED JAN. 1983  
REVISED OCT., 1995