

COPY

ALLEGAN COUNTY REMONUMENTATION
LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Allegan
(County)

Located in:

Corner Code #

other
#3

1. Public Land Survey

T R FG-1 Heath Twp.
T R * FG-13 Overisel Twp.
T R (6th #3) both Tups)

2. Property Controlling
in Section

S 4 T 3N R 14W Heath Twp.
S 33 T 4N R 14W Overisel Twp.

3. Miscellaneous
Property in Sec.

S T R
S T R

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

I, Kirk L. Van Order, in a field survey on Nov. 21, 1996, do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and for that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below.

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	16		17		18		19		20		21		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

A. Description of original monument and accessories and/or subsequent restoration:

APPROVED REMONUMENTATION CORNER
P.A. 345 OF 1990
ALLEGAN COUNTY

DATE APPROVED 11-26-96
COUNTY REP. Kirk L. Van Order

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Set standard Allegan County witness monument on township line on top of East bank of swamp AZ 271°14'02" 1624.20 feet from G-13 and AZ 91°41'02" 1012.19 feet from computed position F-13. Also being AZ 91°14'02" 948.20 feet from computed position F-1, T.3N., R.14W.

1624.20' on road traverse.

This position not established by original government surveyors. This monument is accepted as the best available evidence of the position of the corner.

Peer group approved Nov. 26, 1996.

(See back of sheet for sketch)

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Set standard Allegan County witness monument (3/4" x 36" steel rod w/yellow cap #23520)

Nail & Remon. tag in N side 11" Maple	AZ 285°	22.29'
Nail & Remon. tag in SE side 11" Maple	AZ 255°	30.58'
Nail & Remon. tag in E side 6" Ash	AZ 195°	25.69'
Nail & Remon. tag in N side 7" Maple	AZ 100°	2.75'
Page wire fence running East & West	AZ 180°	7' +/-

Signed by

Surveyor's Michigan License No. 23520

Date 12-31-96



USER0005 PAGE 403

FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, P.L.A. 1971
REVISED JULY 14, 1975
REVISED JAN. 1983
REVISED OCT., 1986

COPY

FG-1 HEATH TWP.
FG-13 OVERISEL TWP.

N.
C

