

ALLEGAN COUNTY REMONUMENTATION
LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Allegan
(County)

Located In:

Corner Code #

other #4

1. Public Land Survey

T___ R___
T___ R___
T___ R___
T___ R___

CD-13 Overisel Twp.

2. Property Controlling
in Section

S 32 T 4N R 14W

Overisel Twp.

3. Miscellaneous
Property in Sec.

S___ T___ R___
S___ T___ R___

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____

5. Private Claims _____

I, Kirk L. Van Order, in a field survey on Dec. 2, 1996 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6	5	4	3	2	1							
3													
4	7	8	9	10	11	12							
5													
6	19	17	16	15	14	13							
7													
8	19	20	21	22	23	24							
9													
10	30	29	28	27	26	25							
11													
12	31	32	33	34	35	36							
13													

A. Description of original monument and accessories and/or subsequent restoration:

APPROVED REMONUMENTATION CORNER

P.A. 345 OF 1990

ALLEGAN COUNTY

DATE APPROVED

11-26-96

COUNTY REP.

Kirk L. Van Order

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Set standard Allegan County witness monument on South line of Section 32 on top of West bank of swamp being West 577.71 feet from position D-13.

This position not established by original government surveyors. This monument is accepted as the best available evidence of the position of the corner.
Peer group approved Nov. 26, 1996.
Distance traversed 2037.82 feet offroad.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Set standard Allegan County witness monument (3/4" x 36" steel rod w/yellow plastic cap #23520) at top of bank West of D-13.

Nail & Remon. tag in NE side 15" Oak	AZ 305°	8.60'
Nail & Remon. tag in NE side 10" Cherry	AZ 315°	21.82'
Nail & Remon. tag in W side 9" Oak	AZ 170	13.59'
Nail & Remon. tag in SE side 9" Oak	AZ 245°	3.56'

Signed by Kirk L. Van Order
Surveyor's Michigan License No. 23520

Date 12-31-96



100005 PAGE 492

FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 14, 1975
REVISED MAY 14, 1975
JAN. 1983
REVISED OCT., 1995