

ALLEGAN COUNTY REMONUMENTATION
LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Allegan
(County)

Located In:

Corner Code #

other
#5

1. Public Land Survey

T___ R___ D 12-13
T___ R___ Overisel Twp.
T___ R___ (#5)
T___ R___

2. Property Controlling
in Section

S 32 T 4N R 14W Overisel Twp.

3. Miscellaneous
Property in Sec.

S___ T___ R___
S___ T___ R___
S___ T___ R___

97 JAN 22 PM 1:27
FILED
Register of Deeds
Allegan County, Michigan

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

I, Kirk L. Van Order, in a field survey on Dec. 12, 1996 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law, established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2		6		5		4		3		2		1	
3													
4		7		8		9		10		11		12	
5													
6		18		17		16		15		14		13	
7													
8		19		20		21		22		23		24	
9													
10		30		29		28		27		26		25	
11													
12		31		32		33		34		35		36	
13													

A. Description of original monument and accessories and/or subsequent restoration:

APPROVED REMONUMENTATION CORNER
P.A. 345 OF 1990
ALLEGAN COUNTY

DATE APPROVED 12-10-96
COUNTY REP. Kirk L. Van Order

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Set standard Allegan County witness monument on North and South 1/4 line of Section 32 on a straight line extension from D-11 thru D-12 to a point on the top of the North bank of a swamp, said point being North 526.57 feet from D-13 position.

This position not established by original government surveyors. This monument is accepted as the best available evidence of the position of the corner.

2134.83' off road traverse.

Peer group approved Dec. 10, 1996.


C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Set standard Allegan County witness monument (3/4" x 36" steel rod w/yellow cap #23520)

SE corner conc. block house fndn.	AZ 295°	70.73'
Nail & Remon. tag in SE side 24" Beech	AZ 245°	32.30'
Nail & Remon. tag in SE side 20" Red Oak	AZ 215°	22.72'
Nail & Remon. tag in SE corner 4" x 4" treated fence corner post	AZ 50°	1.44'

Signed by Kirk L. Van Order
Surveyor's Michigan License No. 23520

Date 12-31-96



USE: 0005 PAG: 493

FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 25, 1971
REVISED, MAY 14, 1975
REVISED, JAN. 1983
REVISED, OCT., 1995