

SURVEY &
REMONUMENTATION

APR 07 1998

ALLEGAN COUNTY REMONUMENTATION
LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in SECTION

Allegan
(County)

Located In:

Corner Code #

1. Public Land Survey

T R ✓ DE-1
T R Heath Twp. (Seq #4)
T R ✓ DE-13
T R Overisel Twp. (#6)

2. Property Controlling
in Section

S 5 T3N R14W
S 32 T4N R14W
S T R
S T R

3. Miscellaneous
Property in Sec.

S T R
S T R

98 JAN 21 PM 1:23
REGISTER OF DEEDS
ALLEGAN COUNTY, MICH.
J. L. E. E. E.

FILED

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

I, Kirk L. Van Order, in a field survey on Oct. 26, 1997, do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and for that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law, established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	10		11		12		13		14		15		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

A. Description of original monument and accessories and/or subsequent restoration:

APPROVED REMONUMENTATION CORNER
P.A. 345 OF 1990
ALLEGAN COUNTY
DATE APPROVED 11-11-97
COUNTY REP. K.V.O.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Set standard Allegan County witness monument on North and South lines of Section 5, T.3N., R.14W. and Section 32, T.4N., R.14W. respectively on highland East of bayou being

AZ 91°14'02" 1382.47 feet from computed position D-1,
AZ 271°14'02" 1258.04 feet from computed position E-1,
AZ 91°-14'02" 1452.33 feet from computed position D-13, and
AZ 271°14'02" 1182.14 feet from computed position E-13.

This position not established by original government surveyors. This monument is accepted as the best available evidence of the position of the corner.

Peer group approved Nov. 11, 1997.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Set standard Allegan County witness monument (3/4" x 36" steel rod w/yellow plastic cap #23520)

Nail & Remon. tag in S side 17" Hemlock	AZ 285°	18.96'
Nail & Remon. tag in E side 20" Hemlock	AZ 350°	23.33'
Nail & Remon. tag in NE side 10" Hemlock	AZ 100°	21.54'
Nail & Remon. tag in W side 25" Maple	AZ 180°	31.88'

Signed by Kirk L. Van Order
Surveyor's Michigan License No. 23520

Date 12-31-97

