

SURVEY
REMONUMENTATION

APR 29 1999

SECTION

ALLEGAN COUNTY REMONUMENTATION
LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Allegan (County)	Located In:	Corner Code #
1. Public Land Survey	T <u> </u> R <u> </u>	E 12-13
	T <u> </u> R <u> </u>	Overisel Twp. (Seq. #12)
	T <u> </u> R <u> </u>	
	T <u> </u> R <u> </u>	
2. Property Controlling in Section	S 32 T4N R14W	Overisel Twp.
	S 33 T4N R14W	Overisel Twp.
3. Miscellaneous	S <u> </u> T <u> </u> R <u> </u>	
Property in Sec.	S <u> </u> T <u> </u> R <u> </u>	

FILED

1/28/1999 2:44:39 PM

JOYCE A. WATTS
REGISTER OF DEEDS
ALLEGAN COUNTY, MICH

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat
5. Private Claims

I, Kirk L. Van Order, in a field survey on Oct. 13, 1997 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

A. Description of original monument and accessories and/or subsequent restoration:

E-13 falls in Rabbit River

APPROVED REMONUMENTATION CORNER
P.A. 345 OF 1990
ALLEGAN COUNTY
DATE APPROVED DEC. 22, 1998
COUNTY REP. Kirk L. Van Order

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Set standard Allegan County witness monument on East and West lines of Section 32 and Section 33, T.4N., R.14W. respectively on highland North of Rabbit River being

N. 00°56'34" W. 152.15 feet from computed position E-13 and

S. 00°56'34" E. 2497.51 feet from E-12

This position not established by original government surveyors. This monument is accepted as the best available evidence of the position of the corner.

Peer group approved Dec. 22, 1998.

Traversed distance 2649.66' off road

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Set standard Allegan County witness monument (3/4" x 36" steel rod w/yellow plastic cap #23520)

Nail & Remon. tag in NE side 20" w. oak	AZ 320°	5.24'
Nail & Remon. tag in NE side 5" w. oak	AZ 125°	6.87'
Nail & Remon. tag in NW side 13" sassafras	AZ 200°	13.90°
Nail & Remon. tag in NW side 9" beech	AZ 245°	30.44'

Signed by Kirk L. Van Order
Surveyor's Michigan License No. 23520

Date 1-13-1999

SURVEY
REMONUMENTATION

APR 29 1933

SECTION

E 12-13 (SEA. #12)
OVERISEL TWP.

LIBERO 007 PAGE 39

