1999 Alpena County Remonumentation Corner LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

REW DISCUSSION OF

JAN 2 1 2000

For corr	ners in			,	And the fact of the
	Alpena (County)	Located In:	Corner Code #	·	SECTION
1. Pub	lic Land Survey	T <u>29N</u> R <u>5E</u> T <u>29N</u> R <u>6E</u> T R T R	<u>M-6 √</u> <u>A-6</u> -		IIIII L- 2 P- 271
2. Property Controlling S T R I I2/10/1999 01:39P in Section S T R Kathy J. Matash, Register Alpena Co., MI LDC 9.00 3. Miscellaneous S T R R Register of Deeds Stamp & File Numb					
1101	berty in Sec.			<u> </u>	-
4. Lot No, Recorded Plat ABCDEFGHIJKLM					
5. Priva	ate Claims			2 6 3	5 4 3 2 1
I, <u>Daniel T. Kibbe</u> , in a field survey on <u>June 14</u> , 19 99 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:					
NOTE:		ners, all in the same town and ran	ge, may be recorded	11	
	on this certificate			12 -31	32 33 34 35 36
A. Description of original monument and accessories and/or subsequent restoration:					
 1839: GLO Survey by Lewis Clason. Set 1/4 post. Referenced: Y. Pine 5-S19W-26/Aspen 6-N49W-21. 1908: County Survey by Jos. W. McNeil. Did not find any Corner or OBT's, everything burned. Set large cedar stake. Referenced: Green Norway 7-S59W-55. 1959: MDOT Survey by N.C. Caldwell. Dug 4'x4'x3' and could not locate old corner. Set 1" bar by single proportion. 1.23' Rt. Sta. 306+62.18. Fenced in line East and West. Referenced: 18" N. Pine-S85W-99.09'/24" Oak-N58W-86.70'/16" N. Pine-N65E-83.22' 1959: MDOT Recorded Corner by N.C. Caldwell. Dug 4'x4'x3' and could not locate old corner. Set 1" bar by single proportion 1.23' Rt. Sta 306+62.18'. Fenced in line East and West. Referenced: 18" N. Pine-S85W-99.09'/24" Oak-N58W-86.70'/16" N. Pine-N65E-83.22'. 1959: MDOT Road Plans by N.C. Caldwell. Found 3/4" pipe. Referenced: 18" N. Pine-N85W-98.91'/24" Oak-N58W-86.38'/9" Oak-N75E0 104.40' 1962: Witness Records by Porter Survey. 1 1/4" pipe in mon. box 1.23' Rt. of C/L of M-65. (Gerald Wozniack) Referenced: 18" N. Pine-S85W-98.91'/24" Oak-N58W-86.38'/9" Oak-N753-104.40' 1994: MDOT Recorded Corner by Clifford C. Lindgren. Found 1 1/4" pipe in mon. box after construction 2' East of M-65 C/L. Referenced: N/Tag P. Pole-N45E-139.14'/N/Tag 30" Oak-West-87.80'/N/Tag 12" R. Pine-S40W-99.22' 1994: Recorded Corner by Clifford C. Lindgren. Found 1 1/4" pipe in mon. box after construction? East of M-65 C/L 2.87' East before construction, undisturbed. Referenced: N/Tag P. Pole-N45E-139.14'/N/Tag 30" Oak-West-87.80'/N/Tag 22" Oak-N70E-104.35'/N/Tag 12" R. Pine-S40W-99.22'. 1998: Recorded Corner by Joseph C. Kapelczak. Found 1 1/4" pipe in mon. box 1.2' East of centerline of M-65 re-used recovered witnesses from Liber1, page 291. Referenced: N/Tag P. Pole-N45E-139.14'/N/Tag 30" Oak-West-87.80'/N/Tag 22" Oak-N70E-104.35'/N/Tag 12" R. Pine-S40W-99.22'. 1998: Remon. Survey by Daniel T. Kibbe. Found 1 1/4" pipe in mon. box 1.2' East of CL M-65. <li< td=""></li<>					
C.					
1999:	Referenced: P. Pole-set Twin Oak 30" Oak-se	unty cap stamped to identify the co tag-N32 E 139.01 8"-set tag-S83 E 102.80' t tag-N86 W 87.06' e-set tag-S39 W 101.67'	mer over 1/2" iron tod inside 1		PENA COUNTY
Signed by Date November 30, 1999					
Surveyor's Michigan License No. 37278					
DANIEL T. KIBBE LAND LAND SURVEYOR SURVEYOR SURVEYOR REVISED MAY 14, 1975 REVISED JAN., 1983 REVISED OCT., 1995					