

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. PA 1970

For Corners In:

Alpena
(County)

Located In

Corner Code #

1. Public Land Survey	T	29N	R	8E	E-1
	T	29N	R	8E	F-1
2. Property Controlling in Section	S	T	R		
	S	T	R		
3. Miscellaneous Property in Section	S	T	R		
	S	T	R		

4. Lot No: _____ Recorded Plat: _____

5. Private Claims: _____

I, Carl T. Kiiskila, in a field survey on June 30, 2010 do hereby state that under requirements of PA 74, Michigan PA of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

A. Description of original monument and accessories and/or subsequent restoration:

E-1 - Sec. Cor. comm. to sec.'s 4&5, T29N,R8E

F-1 - North 1/4 Corner Section 4, T29N,R8E

1839 - GLO - Lewis Claison - Intersected S. Boundary T30N 33 links W. of post.
W. Birch 7" S45°E 25 Links
Cedar 8" S33°W 27 Links

Corner not set during the Original GLO Survey

1996 - Wayne T. Lewis P.S.#41922 set a 1/2" bar w/ P.S. cap while doing a survey in section 5. No witnesses given

B. Description of corner evidence found and/or method applies in restoring or re-establishing corner:

E-1 - Sec. Cor. comm. to sec.'s 4&5, T29N,R8E

F-1 - North 1/4 Corner Section 4, T29N,R8E

Found a 1/2" bar with P.S. cap #41922 fitting Wayne T. Lewis's Survey and record GLO distance East reasonably well.

Established the North 1/4 Corner Section 4 midway between the NE corner of section 4 and the NW corner of section 4 on the South boundary of T30N, R8E.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

E-1 - Sec. Cor. comm. to sec.'s 4&5, T29N,R8E

F-1 - North 1/4 Corner Section 4, T29N,R8E

1/2" bar with P.S. cap #41922

Set a 1"x32" galvanized pipe with Standard DNR Cap

Witnesses:

S65°E 8.63' to set N&T on SW side 10" R. Maple
S11°E 12.15' to set N&T on E side 9" Cedar
S83°W 20.86' to set N&T on N side 7" Cedar
N26°W 4.71' to set N&T on E side 10" Cedar
N87°E 21.65' to found concrete monument section corner common to sections 32& 33 T30N,R8E

Witnesses:

N16°E 30.38' to set N&T on W side 6" Balsam Fir
S89°E 16.70' to set N&T on N side 4" Balsam Fir
S30°E 9.87' to set N&T on W side 12" Cedar
S63°W 15.35' to set N&T on S side 6" Balsam Fir
East 48.75' to set DNR monument
East - West barbed wire North 14'
Set Blue Carsonite Post 1' North

Signed by:

Carl T. Kiiskila

Date:

2/9/11

Surveyor's Michigan License No.:

33981

