

JAN 21 2000

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

SECTION

For corners in
Alpena
 (County)

Located in:

Corner Code #

1. Public Land Survey

T 29N R 8EK-11

T _____ R _____

Sanborn Twp.

T _____ R _____

T _____ R _____

2. Property Controlling
in Section

S _____ T _____ R _____

S _____ T _____ R _____

3. Miscellaneous

S _____ T _____ R _____

Property in Section

S _____ T _____ R _____



L- 2 P- 243

11/22/1999 01:43P

Page: 1 of 1

Kathy J. Matash, Register Alpena Co., MI LDC 9.00

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____

5. Private Claims _____

I, Thomas L. Fabis, in a field survey on July 27, 1999,
 do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned
 in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current
 manual of survey instructions of the United States Department of the Interior, Bureau of Land
 Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and
 5 above were in conformance with the rules of the Michigan Board of Professional Surveyors or by a
 Decree of a Court of Law; established, re-established, monumented; re-monumented, recovered, found
 as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded
 on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

1839: G.L.O. Survey Lewis Clason set post & referenced: W. Pine 24 N44½W 22, Y.Pine 16 S56½E 40.
 1902 & 1906: County Surveys Jos. W. McNeil cedar stake 5" sq. & referenced.
 1970's: M.D.O.T. R.O.W. Maps Ford axle and referenced.
 1972: L.C.R.C. Don Marlatt existing iron & referenced.
 1980: Survey & L.C.R.C. David Guthrie existing angle iron raised with 1/2" iron & referenced.
 1983 & 1988: Surveys by Earl T. Lewis existing 1/2" Rod & referenced.
 1991 & 1997: Surveys by David Guthrie existing 1/2" Iron Rod & referenced.
 1995: Surveys Liber 2 Page 921 and 879 Thomas Fabis Exis. 1/2" iron rod & referenced.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

1999: Found 1/2" iron rod in center of E-W gravel road (Scott Rd.). Found 3 existing
 witnesses as listed in Part C further confirming the location of this corner as
 being the same used by the previous surveyors mentioned in Part A.

The position of this corner is compatible with county and local surveys and is
 accepted as a careful and faithful perpetuation of the position of the original
 corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

1999: Set 3" dia. alum. cap, stamped to identify the corner, over the existing 1/2" iron
 rod. Witnesses are:

Ex. Shiner in P. Pole N17W 30.13
 Ex. WTL Tag in W. Pine N45E 90.20
 Ex. WTL Tag in 7" Oak S70W 55.52
 Set Tag P.S. #31591 in 5" Maple S8E 40.53

P.A. 345 ALPENA COUNTY
 PEER APPROVED 8/26/99

Thomas L. Fabis

Signed by

Thomas L. Fabis

Date November 19, 1999Surveyor's Michigan License No. 31591