

# LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. PA 1970

For Corners In:

Alpena  
(County)

Located In

Corner Code #

1. Public Land Survey	T	30N	R	8E	F-13
	T	30N	R	8E	H-13
2. Property Controlling in Section	S	T		R	
	S	T		R	
3. Miscellaneous Property in Section	S	T		R	
	S	T		R	

4. Lot No: \_\_\_\_\_ Recorded Plat: \_\_\_\_\_

5. Private Claims: \_\_\_\_\_

I, Carl T. Kiiskila, in a field survey on September 29, 2010 do hereby state that under requirements of PA 74, Michigan PA of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

**NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.**

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5			4		3		2		1	
3													
4	7		8			9		10		11		12	
5													
6	18		17			16		15		14		13	
7													
8	19		20			21		22		23		24	
9													
10	30		29			28		27		26		25	
11													
12	31		32			33		34		35		36	
13													

A. Description of original monument and accessories and/or subsequent restoration:

F-13 – South ¼ Corner section 33, T30N,R8E

1839 – GLO – Lewis Claison set ¼ Section post  
Wits.  
Hem. 18" N42°W 11 links  
Hem. 16" N25°E 09 links

H-13 – South ¼ Corner section 34, T30N,R8E

1839 – GLO – Lewis Claison set ¼ section post  
Wits.  
Tam. 10" N49°E 35 links  
Fir 6" S17°W 25 links  
1903 – County Surveyor Records – J.W.McNeil used corner previously set by him from O.B.T.s while doing a survey for Highway Commissioner J.L. Mathews.  
no witnesses were given.

2006 – Gary W. St.Charles P.S.#27461 set ½" Rebar/Cap  
for corner no witnesses were given

B. Description of corner evidence found and/or method applies in restoring or re-establishing corner:

F-13 – South ¼ Corner section 33, T30N,R8E

Set a 1"x48" pipe with Standard DNR Cap by single proportionate measurement between the Southeast and Southwest corners of section 33.

H-13 – South ¼ Corner section 34, T30N,R8E

Found and accepted a ½" bar with P.S.#27461 fitting GLO distance East and West reasonably well and J.W.McNeil's distance West to the center line of existing railroad well.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

F-13 – South ¼ Corner section 33, T30N,R8E

1"x48" pipe with Standard DNR Cap

Witnesses:

N75°E 7.75' to set N&T on N side 13" Oak  
S44°E 24.18' to set N&T on SW side 6" Balsam Fir  
S51°W 32.05' to set N&T on SE side 14" R. Maple  
N22°W 11.94' to set N&T on NE side 5" Balsam Fir  
West 48.75 to set DNR Monument North ¼  
Corner section 4, T29N,R8E

Set Blue Carsonite Post w/loc. tag 1' North

H-13 – South ¼ Corner section 34, T30N,R8E

Drove a 1"x48" galvanized pipe with Standard DNR Cap over found ½" bar

Witnesses:

N52°E 38.82' to set N&T on SE side 12" R. Maple  
S01°W 13.78' to set N&T on W side 14" Poplar  
N10°W 16.79' to set N&T on W side 9"&12 Twin Balsam Fir  
S60°W 18.35' to set N&T on N side 18" R.Maple  
N89°W 59.45' to set DNR Monument North ¼  
Corner section 3, T29N,R8E

Set Blue Carsonite Post w/loc. tag 1' North

Signed by:

Carl T. Kiiskila

Date:

2/9/11

Surveyor's Michigan License No.:

33981

