

DEC 0 3, 1993

005688

COMMISSION

1993 Alpena County Remonumentation Corner

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970

RECORDED  
ALPENA COUNTY MI.

LIBER 1 PAGE 255  
SEP 10 9 39 AM '93

*Myriam A. Johnston*  
REGISTER OF DEEDS

For corners in

Alpena

(County)

Located in:

Corner Code =#

1. Public Land Survey

T 32N R 8E

D-9

2. Property Controlling  
in Section

S T R

3. Miscellaneous  
Property in Sec.

S T R

4. Lot No. , Recorded Plat

5. Private Claims

Register of Deeds Stamp & File Number

I, David B. Guthrie, in a field survey on July 12, 19 93,

do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

- 1855: G.L.O Re-survey by Josiah Knauer - Set post and referenced: Beech 8 - S39W - 16 / Beech 10 - N31E - 29  
1888: County survey by Fred A. Rice - Found G.L.O Corner

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

- 1993: Found 1/2" iron rod by Porter's Survey. This corner lies in the Center of Naylor Road in line with Boundary Fencelines North and South. The position is compatible with former County Survey s.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

- 1993: Set 1/2" x 24" iron rod with a 3" aluminum cap stamped to identify the corner. Referenced:  
N48°W - 3" Basswood - 36.26 feet  
S60°W - Utility Pole - 80.04 feet  
S05°E - 6" Apple - 47.02 feet  
N74°E - 4" Maple - 55.75 feet



Signed by

*David B. Guthrie*

Date

9/14/93

Surveyor's Michigan License No.

22435