

# LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. PA 1970

|  |                         |               |
|--|-------------------------|---------------|
| For Corners In:<br><u>Antrim</u><br>(County) | Located In              | Corner Code # |
| 1. Public Land Survey                        | T <u>29</u> R <u>6W</u> | <u>M-10</u>   |
|  | T <u>29</u> R <u>6W</u> | <u>M-11</u>   |
| 2. Property Controlling in Section           | S _____ T _____ R _____ | _____         |
|  | S _____ T _____ R _____ | _____         |
| 3. Miscellaneous Property in Section         | S _____ T _____ R _____ | _____         |
|  | S _____ T _____ R _____ | _____         |
| 4. Lot No: _____                             | Recorded Plat: _____    |               |
| 5. Private Claims: _____                     |                         |               |

Register of Deeds Stamp & File Number

|    |    |   |    |   |    |   |    |   |    |   |    |   |   |
|----|----|---|----|---|----|---|----|---|----|---|----|---|---|
|    | A  | B | C  | D | E  | F | G  | H | I  | J | K  | L | M |
| 1  |    |   |    |   |    |   |    |   |    |   |    |   |   |
| 2  | 6  |   | 5  |   | 4  |   | 3  |   | 2  |   | 1  |   |   |
| 3  |    |   |    |   |    |   |    |   |    |   |    |   |   |
| 4  | 7  |   | 8  |   | 9  |   | 10 |   | 11 |   | 12 |   |   |
| 5  |    |   |    |   |    |   |    |   |    |   |    |   |   |
| 6  | 18 |   | 17 |   | 16 |   | 15 |   | 14 |   | 13 |   |   |
| 7  |    |   |    |   |    |   |    |   |    |   |    |   |   |
| 8  | 19 |   | 20 |   | 21 |   | 22 |   | 23 |   | 24 |   |   |
| 9  |    |   |    |   |    |   |    |   |    |   |    |   |   |
| 10 | 30 |   | 29 |   | 28 |   | 27 |   | 26 |   | 25 | ● |   |
| 11 |    |   |    |   |    |   |    |   |    |   |    | ● |   |
| 12 | 31 |   | 32 |   | 33 |   | 34 |   | 35 |   | 36 |   |   |
| 13 |    |   |    |   |    |   |    |   |    |   |    |   |   |

I, Carl T. Kiiskila, in a field survey on October 24, 2000 do hereby state that under requirements of PA 74, Michigan PA of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law, established, re-established, monumented, recovered, found as expressed below:

**NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.**

**A. Description of original monument and accessories and/or subsequent restoration:**

M-10 GLO – H. Brevoort & J.H. Mullett D.S. – 1839  
 Beech 12 for ¼ Section Post  
 Wit: None Given

Kenneth J. Ostling RLS #10068. Found a ¾" pipe at midpoint between section corners. May 13, 1957 set 1" pipe with Brass cap  
 Wit: 8" Cherry N15°W 107 links  
 8" Cherry S60°W 38.5 links

Liber 2, Page 74 Beryl M. Jones LLS #23541, found DNR monument Sept. 15, 1981.  
 Wit: S76°E 12" J. Pine 41.20'  
 N14°W 14" Cherry 71.02'  
 S67°W 15" Cherry 25.15'

M-11 GLO – H. Brevoort & J.H. Mullett D.S. – 1839  
 Set Post Corner Sections 25 & 36  
 Wit: Sugar 12 S45°W 18 Links  
 Elm 12 N67°W 20 Links

Kenneth J. Ostling RLS #10068. Found a ¾" pipe in the center of a old road grade north and trail road east. May 13, 1957 set 1" pipe with brass cap.  
 Wit: 6" Elm S03°W 48.5 links  
 8" Elm N60°W 37 links  
 8" Elm N22°E 104.5 links

L.2, Page 74 Beryl M. Jones LLS #23541 found DNR monument.  
 Wit: S76°E 18" Poplar 59.20'  
 S21°W 12" Cherry 53.45'  
 S54°W 20" Bass 79.50'

**B. Description of corner evidence found and/or method applies in restoring or re-establishing corner:**

M-10 Re-established the East quarter corner of section 25 using Beryl Jones distances North and South and one existing NBT.

M-11 – Found 1" pipe with the brass cap broken off.

**C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:**

M-10 – Set DNR Monument  
 Wit 4 Cherry S74°W 42.31  
 8 Cherry N17°E 105.56  
 \* 8 Jack pine S69°E 41.28  
 \*10 Cherry N70°E 141.87  
 Ctr. N-S Road East 2'±

M-11 – Found 1" Iron Pipe  
 Wit: 5 Twin Cherry N51°W 33.06  
 \*12 Cherry S37°W 53.96  
 12 Cherry S12°E 47.45  
 8 Cherry East 77.09  
 Ctr. N-S & E Trail Roads

\* Old witnesses by others

\* Old witnesses by others

Signed by: Carl T. Kiiskila  
 Surveyor's Michigan License No.: 33981

Date: 4-16-02

