

# LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. PA 1970

For Corners In:  
Antrim \_\_\_\_\_ Located In \_\_\_\_\_ Corner Code # \_\_\_\_\_  
(County)

1. Public Land Survey		T	<u>29N</u>		R	<u>6W</u>		K-13
		T	<u>29N</u>		R	<u>6W</u>		L-12
2. Property Controlling in Section	S	T	_____		R	_____		_____
	S	T	_____		R	_____		_____
3. Miscellaneous Property in Section	S	T	_____		R	_____		_____
	S	T	_____		R	_____		_____

4. Lot No: \_\_\_\_\_ Recorded Plat: \_\_\_\_\_

5. Private Claims: \_\_\_\_\_

I, Carl T. Kiiskila, in a field survey on September 18, 2000 do hereby state that under requirements of PA 74, Michigan PA of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law, established, re-established, monumented, recovered, found as expressed below:

**NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.**

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

A. Description of original monument and accessories and/or subsequent restoration:

K-13 GLO- H. Brevoort & J.H. Mullett D.S. – 1839 Set	L-13 GLO- H. Brevoort & J.H. Mullett D.S. – 1839
Post Corner Sections 35 & 36	Set ¼ Section Post
Wit: Sugar 16 N32°E 16 Links	Wit: Sugar 14 N20°W 16 Links
Beech 12 N37°W 9 Links	Sugar 12 N32°E 21 Links

Peter E. Chenard R.L.S. #14200 Sept. 1972 L.C.R.C. L. 1  
P.110 Set ½" X 18" bar and cap by proportionate measurement  
Wit: N02°E Tag 24" Maple 9.38', S85°E Tag 7" maple 11.82', S65°W Tag 7" Maple 31.59'

B. Description of corner evidence found and/or method applies in restoring or re-establishing corner:

K-13 Found ½ Rerod W/PS Cap #14200, Peter E. Chenard	L-13 Re-established the South quarter corner of section 36 by single proportionate measurement between corners K-13 and M-13.
--	---

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

K-13 Set DNR Monument	L-13 Set DNR Monument
Wit: *24" Maple N08°E 10.61'	Wit: 16" Cherry N84°W 43.73'
* 7" Maple S82°E 12.07'	5" Maple North 40.77'
5" Maple S13°W 31.72'	5" Maple S50°E 54.97'
* 6" Maple S74°W 31.61'	8" Cherry S48°W 17.29'
Carsonite Post North 1±	Carsonite Post North 1±
	Ctr. E-W Trail Road North 72±

\*Old Witness By Others

Signed by: Carl T. Kiiskila  
Surveyor's Michigan License No.: 33981

Date: 4-15-02

