

SURVEY & REMONUMENTATION

JAN 23 2001

Liber 00003 Page 0134

SECTION

LAND CORNER RECORDATION CERTIFICATE ANTRIM COUNTY MI. Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

<u>Antrim</u> (County)	Located In:	Echo Corner Code #
1. Public Land Survey	NE 14	T 31N R 7W K-5
		T R
		T R
		T R
2. Property Controlling in Section	S	T R
	S	T R
3. Miscellaneous Property in Sec.	S	T R
	S	T R

12-18-2000 18:23:09

Manda R. Conway
REGISTER OF DEEDS

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

I, Terry B. Smith, in a field survey on December 07, 2000 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A	B	C	D	E	F	G	H	I	J	K	L	M
1												
2	6	5	4	3	2	1						
3												
4	7	8	9	10	11	12						
5												
6	18	17	16	15	14	13						
7												
8	19	20	21	22	23	24						
9												
10	30	29	28	27	26	25						
11												
12	31	32	33	34	35	36						
13												

A. Description of original monument and accessories and/or subsequent restoration:

1857 Govt. Hemlock post
Beech 11 N22E 23 lks
Beech 10 S72W 20 lks.
1905 B. L. Caulkin, County Surveyor section subdivision
1972 reestablished by G. DeLaMater by "modified" double propornate measure

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

found concrete monument per LCRC Liber 204 page 47
peer group "locally accepted corner"



C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

NE Corner Section 14, T31N, R7W
set antrim county monument beside concrete monument
16" Cherry S25E 31.75
14" Cherry S75E 25.00
18" Maple S10E 24.65
12" Poplar N85E 63.50

Ratified by Peer Group
In accordance with
P.A. 345
Antrim Co. Chairman

Arthur L. Lennox

Arthur L. Lennox, P.E., P.S.
Nov. 28, 2000

Signed by TB Smith
Surveyor's Michigan License No. 25873

Date 12-18-2000