

APR 06 1999

SECTION

ARENAC COUNTY REMONUMENTATION
LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

ARENAC
(County)

Located In: Corner Code #

1. Public Land Survey T 18N R 4E
T R
T R
T R

2. Property Controlling S T R
in Section S T R

3. Miscellaneous S T R
Property in Sec. S T R

Page 1 of 1
ROSE SMITH
ARENAC CO. REG. OF DEEDS
Rec. Date 12/29/98 Time 10:51
RECORDING FEES: 9.00

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat
5. Private Claims

I, DALE L. WINIECKE, in a field survey on JULY 29, 1998 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and for that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

- G-7
1. ORIGINAL POST SET IN 1843 BY J. BURT, D.S.
HEMLOCK 12" S78°W 23 LINKS
HEMLOCK 22" N80°E 34 LINKS
 2. COUNTY SURVEYOR NOTES, FIELDBOOK 6, PAGE 45 (1908)
 3. LCRC L.1, P.186, N. CALDWELL PS#12018, (1964), SET 'T' IRON AND 1/2" PIPE
 4. CERTIFICATE OF SURVEY, L.1, P.177, L. McGINNIS PS#18999, (1974), FOUND
 5. CERTIFICATE OF SURVEY L.2, P.49-51, W. RUDELL PS#14769, (1993), FOUND IRON STAKE
 6. LCRC L.1, P.331, W. RUDELL PS#14769, (1993), FOUND ANGLE IRON FROM LCRCL.1, P.186

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

G-7
SEARCHED APPARENT LOCATION OF THE CORNER AND FOUND 3/4" PINCH PIPE NEXT TO "T" FENCE POST. EXCAVATED THE CORNER AND FOUND NO OTHER OBJECTS. ALSO FOUND 20D COMMON NAIL NORTHWEST 12.5' OF PIPE. EXCAVATED THIS POINT AND FOUND NO OTHER OBJECTS. CHECKED WITNESSES FROM L.1, P.331, NNE TO N&C IN PP 183.52'(R) 183.36'(M); S37°E MSHD TAG IN PP 59.42'(R) 59.40'(M) ACCEPTED THE PINCH PIPE AS THE BEST AVAILABLE EVIDENCE OF THE POSITION OF THE ORIGINAL CORNER.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

G-7
REPLACED THE 3/4" PIPE WITH A 5/8"X 24" LONG REBAR WITH ARENAC COUNTY REMONUMENTATION CAP.
S55°W 61.14' TO SET NAIL & TAG IN EAST FACE OF POWER POLE
S45°W 126.57' TO THE NORTHEAST CORNER OF A GARAGE #4509
S34°E 59.40' TO MSHD NAIL & TAG IN SOUTHWEST FACE OF POWER POLE
N8°E 183.36' TO NAIL & TAG #14769 IN WEST FACE OF POWER POLE
NORTH 9.35' TO PHYSICAL CENTERLINE OF SAGATOO ROAD
WEST 7.40' TO PHYSICAL CENTERLINE OF DEEP RIVER



Signed by Dale Winiecke
Surveyor's Michigan License No. 41915

Date 12/28/98

FB. 2, P. 68

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, 1971
REVISED MAY 14, 1976
REVISED JAN., 1983

ACCEPTED BY THIS ARENAC COUNTY
SURVEY PEER GROUP AS THE OFFICIAL
CORNER UNDER MICHIGAN PUBLIC ACT
345 OF 1990 AT A MEETING HELD ON
10 NOV. 1998
Paul M. Ciolek
PAUL M. CIOLEK P.S., C.S. (MICHIGAN)