

# LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. PA 1970

For Corners In:

Arenac  
(County)

Located In

Corner Code #

1. Public Land Survey	T	19N	R	3E	E9
	T		R		
2. Property Controlling in Section	S	T	R		
	S	T	R		
3. Miscellaneous Property in Section	S	T	R		
	S	T	R		

4. Lot No: \_\_\_\_\_ Recorded Plat: \_\_\_\_\_

5. Private Claims: \_\_\_\_\_

I, Craig W. McVean, in a field survey on Oct. 6, 2005 do hereby state that under requirements of PA 74, Michigan PA of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

**NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.**

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

A. Description of original monument and accessories and/or subsequent restoration:

E9 – GLO – Set Post – J. Mullett – 1846  
Y. Pine 12" N67°E 33 L.  
W. Pine 10" S38°W 25 L.  
- CPC – Drawing # SF 16944 – Sheet 102 – 1967  
Set iron

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

E9 – Sec. Corner common to Sec. 20, 21, 28 & 29 – Fd. Consumers 'T' iron. No GLO evidence. Centerline of E-W 2-track is 10' ± N. Fits Consumer's Powerline survey. 'T' iron accepted as the best available evidence of the position of the original corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

E9 – Replaced CPC 'T' iron with 3" Arenac Co. Remon. Brass Cap on 5/8" x 4' long iron rebar.  
N41°W 43.92' to set N & T in NE side 20" R. Pine  
S56°W 17.79' to set N & T in NW side 8" Oak  
S50°E 45.93' to set N & T in SW side 22" R. Pine  
N43°E 60.18' to set N & T in NW side 18" R. Pine  
Set Orange Carsonite Post 1' W.



Signed by:

*Craig W. McVean*

Date:

*11/30/2005*

Surveyor's Michigan License No.:

39088