

# LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. PA 1970

For Corners In:

Arenac

(County)

Located In

Corner Code #

1. Public Land Survey T R  
T R  
2. Property Controlling in Section S 30 T 20N R 05E 5  
S T R  
3. Miscellaneous Property in Section S T R  
S T R

4. Lot No: Recorded Plat:

5. Private Claims:

I, Joshua R. Davidson, in a field survey on October 29, 2014 do hereby state that under requirements of PA 74, Michigan PA of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

**NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.**



201600544

Darlene Mikkola  
Register of Deeds  
Arenac County, MI

Page 1 of 1

CD

DOC#: 201600544

February 29, 2016 10:46 AM

Fee: \$14.00

ARENAC CO. REG. 201600544-10145

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

A. Description of original monument and accessories and/or subsequent restoration:

5 – CN 1/16 corner section 30

None

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

5 – CN 1/16 corner section 30

Set 2" stamped aluminum cap on 5/8" x 3/4" rebar per standard BLM procedure. S37°22'W 1.78' to a found 1/2" rebar & cap #16050 not utilized in this survey.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

5 – 2" stamped aluminum cap on 5/8" x 3/4" rebar.

N40°E 29.84' to set nail & tag in SE. side 18" Oak  
S65°E 47.64' to set nail & tag in NE. side 14" Oak  
S16°E 26.86' to set nail & tag in E. side 15" Oak  
S85°W 41.37' to set nail & tag in S. side 12" Oak  
S37°22'W 1.78' to found 1/2" rebar & cap #16050  
Set blue post with location tag 1' Southeast



Signed by:

*Joshua R. Davidson*

Date:

February 24, 2016

Surveyor's Michigan License No.:

46659