

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Baraga (County)	Located In:	Corner Code #
1. Public Land Survey	T R	
	T R	
	T R	
2. Property Controlling in Section	S 7 T 47N R 33W	10
	S 7 T 47N R 33W	3
	S T R	
3. Miscellaneous Property in Sec.	S T R	
	S T R	
4. Lot No. _____, Recorded Plat		
5. Private Claims		

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

I, Stephan J. Szyszkoski, in a field survey on 10 03/29/2012  
3 01/25/2012 do hereby state  
that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2  
above were in conformance with regulations and rules therefore as required in the current manual of survey  
instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of  
a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with  
the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established,  
re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded  
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(10-Sec. 7) South 1/16 corner between Section 7 T47N-R33W and Section 12 T47N-R34W. Not previously  
monumented.

(3-Sec. 7) North 1/16 corner between Section 7 T47N-R33W and Section 12 T47N-R34W. Not previously  
monumented.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(10-Sec. 7) Established the position for the corner midway and on the Range line between Section  
corner 1315.26' south and Quarter corner 1315.26' north.

(3-Sec. 7) Established the position for the corner midway and on the Range line between Section  
corner 1315.26' north and Quarter corner 1315.26' south.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(10) Set 1"IDx32" I.pipe with 4" alum. MDNR cap  
made firm in a mound of rock 3' dia.x 2' high.  
Set measuring nail with MDNR tag in the side of:  
7" Cedar N06E 6.0' mrkd "1/16S BT"  
9" Cedar S10E 32.3' do  
Cedar S39W 22.8' do  
5" twin Sugar N74W 6.2' do  
Set cedar post N59W 2.7' distant.  
Bearings are magnetic.

(3) Set 1"IDx32" I.pipe with 4" alum. MDNR cap.  
Due to rock, the monument leans southerly. The  
center of the cap marks the corner position.  
Set measuring nail with MDNR tag in the side of:  
10" Y.Birch N08E 4.7' mrkd "1/16S BT"  
11" Hemlock S28E 25.7' do  
12" Hemlock S26W 16.6' do  
11" Cedar N44W 29.9' do  
Set sq'd cedar post adjacent.  
Bearings are magnetic.

Signed by Stephan J. Szyszkoski  
Surveyor's Michigan License No. 33986

Date 04/26/2012

For the Michigan Department of Natural Resources, Forest Resources Division

