

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Baraga (County)	Located In:	Corner Code #
1. Public Land Survey	T R	
	T R	
	T R	
2. Property Controlling in Section	S 4 T 48N R 32W	1
	S T R	(GCDB 320700)
	S 4 T 48N R 32W	2
	S T R	(GCDB 360700)
	S T R	
3. Miscellaneous Property in Sec.		
4. Lot No. _____, Recorded Plat		
5. Private Claims		

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

I, Stephan J. Szyszkoski, in a field survey on 06/30/14 do hereby state
that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2
above were in conformance with regulations and rules therefore as required in the current manual of survey
instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of
a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with
the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established,
re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(1-Sec. 4) West 1/16 corner between Section 4 T48N-R32W and Section 33 T49N-R32W. Not previously
monumented.

(2-Sec. 4) East 1/16 corner between Section 4 T48N-R32W and Section 33 T49N-R32W. Not previously
monumented.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(1-Sec. 4) Established the position for the corner on the Township line between Section corner
1319.02' west and Quarter corner 1319.02' east.

(2-Sec. 4) Established the position for the corner on the Township line between Quarter corner
1319.02' west and Section corner 1319.02' east.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(1) Set 1"IDx28" I.pipe with 2" alum. MDNR cap.
The mon. leans slightly north due to sub-surface
rock. The center of the cap marks the position.
Set measuring nail with MDNR tag in the side of:
13" Sugar N41°E 12.4' mrkd "1/16S BT"
6" Balsam S62°E 21.95' do
12" B.Ash S16°E 14.7' do
6" Balsam S63°W 18.25' do
Set sq'd cedar post adjacent.
E= 7898886.442 N= 201943.426

(2) Set 1"IDx28" I.pipe with 2" alum. MDNR cap.
Set measuring nail with MDNR tag in the side of:
9" Maple N04°W 19.9' mrkd "1/16S BT"
9" Maple N79°E 7.9' do
8" Balsam S07°W 12.9' do
7" Balsam S82°W 17.9' do
Set sq'd cedar post adjacent.
E= 7899690.176 N= 201925.054

Bearings are magnetic. Coordinates are MCS83 in meters (NAD83(2011) Datum)
Coord. Ref.=NGS PID RL1468: N= 199449.721 m. E= 7900600.011 m.

Signed by Stephan J. Szyszkoski
Surveyor's Michigan License No. 33986

Date 06/30/2014

For the Michigan Department of Natural Resources, Forest Resources Division

