

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Baraga (County)	Located In:	Corner Code #
1. Public Land Survey	T R	
	T R	
	T R	
2. Property Controlling in Section	S 6 T 48N R 32W	16 (GCDB 160600)
	S 6 T 48N R 32W	14 (GCDB 200620)
3. Miscellaneous Property in Sec.	S T R	
	S T R	
4. Lot No. _____, Recorded Plat		
5. Private Claims		

I, Stephan J. Szyszkoski, in a field survey on 12/03/15 do hereby state  
that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2  
above were in conformance with regulations and rules therefore as required in the current manual of survey  
instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of  
a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with  
the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established,  
re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded  
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(16-Sec. 6) East 1/16 corner between Sections 6 and 7.  
Not previously monumented.

(14-Sec. 6) South 1/16 corner between Sections 5 and 6.  
Not previously monumented.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(16-Sec. 6) Established the position for the corner midway and on the Section line between Quarter  
corner 1320.40' west and Section corner 1320.40' east.

(14-Sec. 6) Established the position for the corner midway and on the Section line between Section  
corner 1319.31' south and Quarter corner 1319.31' north

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(16) Set 1"IDx28" I.pipe with 2" alum. MDNR cap.  
Set measuring nail with MDNR tag in the side of:  
6" Sugar N33°E 13.1' mrkd "1/16S BT"  
5" Sugar S41°E 15.35' do  
3" W.Pine N78°W 3.15' do  
5" Sugar N25°W 15.05' do  
Squared a 2" Balsam S60W 1.0' no nail.  
E= 7896446.803 N= 200416.476

(14) Set 1"IDx28" I.pipe with 2" alum. MDNR cap.  
Set measuring nail with MDNR tag in the side of:  
3" Maple N21°E 9.2' mrkd "1/16S BT"  
4" Maple S71°E 5.1' do  
3" Cherry N82°W 1.05' do  
3" Maple N56°W 9.2' do  
Set sq'd cedar post adjacent.  
E= 7896856.191 N= 200810.650

Bearings are magnetic. Coordinates are MCS83 in meters, NAD83(2011) Epoch 2010.00 datum.  
Coord. Ref.=NGS PID RL1468: N= 199449.725 m. E= 7900599.998 m.

Signed by Stephan J. Szyszkoski Date 03/18/2016  
Surveyor's Michigan License No. 33986

For the Michigan Department of Natural Resources, Forest Resources Division

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2		6		5		4		3		2		1	
3													
4		7		8		9		10		11		12	
5													
6		18		17		16		15		14		13	
7													
8		19		20		21		22		23		24	
9													
10		30		29		28		27		26		25	
11													
12		31		32		33		34		35		36	
13													

