

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Baraga (County)	Located In:	Corner Code #
1. Public Land Survey	T _____ R _____	_____
	T _____ R _____	_____
	T _____ R _____	_____
2. Property Controlling in Section	S 12 T 48N R 33W	14
	S 12 T 48N R 33W	7
	S _____ T _____ R _____	_____
3. Miscellaneous Property in Sec.	S _____ T _____ R _____	_____
	S _____ T _____ R _____	_____
4. Lot No. _____, Recorded Plat _____		
5. Private Claims _____		

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

I, Stephan J. Szyszkoski, in a field survey on 7 03/01/2012 do hereby state
that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2
above were in conformance with regulations and rules therefore as required in the current manual of survey
Instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of
a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with
the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established,
re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(14-Sec. 12) South 1/16 corner between Section 12 T48N-R33W and Section 7 T48N-R32W. Not previously
monumented.

(7-Sec. 12) North 1/16 corner between Section 12 T48N-R33W and Section 7 T48N-R32W. Not previously
monumented.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(14-Sec. 12) Established the position for the corner midway and on the Range line between Section
corner 1314.28' south and Quarter corner 1314.28' north.

(7-Sec. 12) Established the position for the corner midway and on the Range line between Section
corner 1314.28' north and Quarter corner 1314.28' south.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(14) Set 1"IDx32" I.pipe with 4" alum. MDNR cap.
16" Cedar N80E 52.3' mrkd "1/16S BT"
13" W.Pine S19W 26.0' do
5" Balsam S58W 19.75' do
6" B.Spruce N36W 25.65' do
Set sq'd cedar post adjacent.
Bearings are magnetic.

(7) Set 1"IDx32" I.pipe with 4" alum. MDNR cap.
3" Balsam S78E 10.85' mrkd "1/16S BT"
13" Cedar S56W 10.35' do
9" Cedar N78W 19.2' do
6" Cedar N20W 27.5' do
Set sq'd cedar post adjacent.
Bearings are magnetic.

Signed by Stephan J. Szyszkoski
Surveyor's Michigan License No. 33986

Date 03/08/2012

For the Michigan Department of Natural Resources, Forest Resources Division

