

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Baraga (County)	Located In:	Corner Code #
1. Public Land Survey	T _____ R _____ T _____ R _____ T _____ R _____	_____
2. Property Controlling in Section	S 20 T 50N R 33W _____ S 20 T 50N R 33W _____ S _____ T _____ R _____ S _____ T _____ R _____	13 5
3. Miscellaneous Property in Sec.	S _____ T _____ R _____ S _____ T _____ R _____	_____
4. Lot No. _____, Recorded Plat _____		
5. Private Claims _____		

13 07/26/2011

I, Stephan J. Szyszkoski, in a field survey on 5 07/27/2011 do hereby state
that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2
above were in conformance with regulations and rules therefore as required in the current manual of survey
instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of
a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with
the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established,
re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(13-Sec. 20) SE1/16 corner, Section 20. Not established in the original survey.

(5-Sec. 20) North 1/16 corner, Section 20. Not established in the original survey.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(13-Sec. 20) Established the corner at the intersection of straight lines connecting opposite 1/16
corners.

(5-Sec. 20) Established the corner midway and on a straight line between Quarter corner 1319.19'
north and Center of Section 20 1319.19' south.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(13) Set 1"IDx32" I.pipe with 4" alum. MDNR cap.
Set measuring nail with MDNR tag in the side of:
5" Y.Birch N19E 8.85' mrkd "1/16S BT"
5" twin Ash N60E 21.6' do
22" Cedar S01W 22.6' do
6" Ash N71W 40.3' do
Set sq'd Cedar post adjacent.
Bearings are magnetic.

(5) Set 1"IDx32" I.pipe with 4" alum. MDNR cap.
Set measuring nail with MDNR tag in the side of:
4" Maple S73E 21.4' mrkd "1/16S BT"
4" B.Spruce South 13.7' do
8" twin Maple S75W 5.55' do
4" W.Spruce N28W 28.3' do
Set sq'd Cedar post adjacent.
Bearings are magnetic.

Signed by Stephan J. Szyszkoski
Surveyor's Michigan License No. 33986

Date 10/24/2011

For the Michigan Department of Natural Resources, Forest Management Division



16757

16758