

SURVEY &
REMONUMENTATION

FEB 23 1998

SECTION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Baraga

(County)

Located In:

Corner Code #

1. Public Land Survey

T 52N R 33W

#21 North MC

T _____ R _____

between A-12 and

T _____ R _____

A-13

T _____ R _____

2. Property Controlling
in Section

S _____ T _____ R _____

S _____ T _____ R _____

3. Miscellaneous

S _____ T _____ R _____

Property in Sec.

S _____ T _____ R _____

4. Lot No. _____, Recorded Plat _____

5. Private Claims _____

I, Michael Mileski, in a field survey on 3 December, 19 97 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

MC #2; North Meander Corner between A-12 and A-13, T52N, R33W;

Originally established during U.S. Survey conducted by William Burt, D.S. in 1845 and monumented with a wood post witnessed by a

Sugar 16 N56°W 32 lks.

No subsequent record evidence bearing upon the location of this corner was found.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

MC #2; North Meander Corner between A-12 and A-13, T52N, R33W;

This corner was considered lost and reestablished on line at the proportionate distance between the SW corner of section 31 and the W¼ corner of section 31. This corner position falls approximately 28 feet north of the left (north) bank of the Sturgeon River.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

MC #2; North Meander Corner between A-12 and A-13, T52N, R33W;

Set a 1"(I.D.) x 36" galvanized iron pipe and cap stamped as to location projecting 3" above ground.

Set 7" spike	NW/side	9" Balsam	N26°E	37.42'
Set 7" spike	S/side	12" Basswood	S89°E	13.03'
Set 7" spike	NE/side	5" White Ash	N55°W	67.38'
Set 7" spike	W/side	17" Balsam	N01°W	22.33'
		6' Steel fence post w/ yellow sign	South	1.5'

All of the above new bearing trees are marked with upper and lower blazes. The lower blaze is scribed "NBT". Both blazes and a band around the tree at the upper blaze were painted red.

LIBER 4 PAGE 817

Signed by Michael Mileski
Surveyor's Michigan License No. 39091

Date 23 Dec 1997

RECEIVED FOR RECORD THIS 31ST
DAY OF DECEMBER A.D. 1997 AT
10:30 A.M. AND RECORDED IN
LIBER 4 OF LAND CORNER
RECORDATION RECORDS ON PAGE
817.

Hilda Bishop

BARAGA COUNTY REGISTER OF DEEDS
Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2		6		5		4		3		2		1	
3													
4		7		8		9		10		11		12	
5													
6		18		17		16		15		14		13	
7													
8		19		20		21		22		23		24	
9													
10		30		29		28		27		26		25	
11													
12		31		32		33		34		35		36	
13													

APPROVED LAND CORNER
P.A. 345 OF 1990
Baraga County

