

SURVEY &
REMONUMENTATION

FEB 23 1998

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in SECTION

Baraga
(County)

Located In:

Corner Code #

1. Public Land Survey

T 52N R 33W

#3) South MC for
the southernmost
crossing of the
Sturgeon River
between A-11 and
A-12

2. Property Controlling
in Section

S T R

3. Miscellaneous

S T R

Property in Sec.

S T R

4. Lot No. , Recorded Plat

5. Private Claims

I, Michael Mileski, in a field survey on 5 December 19 97 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

MC #3; South Meander Corner for the southernmost crossing of the Sturgeon River between A-11 and A-12, T52N, R33W;

Originally established during U.S. Survey conducted by William Burt, D.S. in 1845 and monumented with a wood post witnessed by an

Elm 8 S40°W 29 lks.

No subsequent record evidence bearing upon the location of this corner was found.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

MC #3; South Meander Corner for the southernmost crossing of the Sturgeon River between A-11 and A-12, T52N, R33W;

This corner was considered lost and reestablished on line at the proportionate distance between the W¼ corner of section 31 and the NW corner of section 31. This corner position falls approximately 65 feet south of the left (south) bank of the Sturgeon River in a 22" sugar maple. A witness corner was established on the section line at a distance of 32.65 feet northerly of the proportioned meander corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

MC #3; South Meander Corner for the southernmost crossing of the Sturgeon River between A-11 and A-12, T52N, R33W;

The witness corner described in Part B was monumented with a 1" (I.D.) x 36" galvanized iron pipe with cap stamped as to location flush with the ground.

Set 7" spike	W/side	21" Sugar Maple	S30°E	58.68'
Set 7" spike	N/side	19" Sugar Maple	S26°W	91.85'
Set 7" spike	N/side	20" Sugar Maple	S57°W	67.21'
Set 7" spike	S/side	8" Sugar Maple	N88°W	75.53'
		6' Steel fence post w/ yellow sign	North	1.5'

All of the above new bearing trees are marked with upper and lower blazes. The lower blaze is scribed "NBT". Both blazes and a band around the tree at the upper blaze were painted red.



LIBER 4 PAGE 818

Signed by Michael Mileski
Surveyor's Michigan License No. 39091

Date 23 Dec 1997