

SURVEY &
REMONUMENTATION

FEB 23 1998

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in SECTION

Baraga

(County)

Located In:

Corner Code #

1. Public Land Survey

T 52N R 33W

#5) South MC for
the northernmost
crossing of the
Sturgeon River
between A-11 and
A-12

2. Property Controlling
in Section

S T R

3. Miscellaneous

S T R

Property in Sec.

S T R

RECEIVED FOR RECORD THIS 31ST
DAY OF DECEMBER A.D. 1997 AT
10:30 A.M. AND RECORDED IN
LIBER 4 OF LAND CORNER
RECORDATION RECORDS ON PAGE
820

Baraga County Register of Deeds

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat

5. Private Claims

I, Michael Mileski, in a field survey on 8 December, 19 97 do hereby state
that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2
above were in conformance with regulations and rules therefore as required in the current manual of
survey instructions of the United States Department of the Interior, Bureau of Land Management or by a
decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in
conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law;
established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

MC #5; South Meander Corner for the northernmost crossing of
the Sturgeon River between A-11 and A-12, T52N, R33W;

Originally established during U.S. Survey conducted by William Burt,
D.S. in 1845 and monumented with a wood post witnessed by a

Fir 12 S77°E 15 lks.

No subsequent record evidence bearing upon the location of this corner was found.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

MC #5; South Meander Corner for the northernmost crossing of the Sturgeon River between
A-11 and A-12, T52N, R33W;

This corner was considered lost and reestablished on line at the proportionate distance between the W¼
corner of section 31 and the NW corner of section 31. This corner position falls approximately 21 feet south
of the right (south) bank of the Sturgeon River.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

MC #5; South Meander Corner for the northernmost crossing of the Sturgeon River between
A-11 and A-12, T52N, R33W;

Set a 1" (I.D.) x 36" galvanized iron pipe with cap stamped as to location
flush with the ground.

Set 7" spike	NE/side	7" White Ash	S43°E	53.68'
Set 7" spike	E/side	6" White Ash	S03°W	71.00'
Set 7" spike	SE/side	11" White Ash	S26°W	96.09'
Set 7" spike	N/side	12" Balsam	S57°W	24.76'
		6' Steel fence post w/ yellow sign	South	2'

All of the above new bearing trees are marked with upper and lower blazes.
The lower blaze is scribed "NBT". Both blazes and a band around the tree
at the upper blaze were painted red.

LIBER 4 PAGE 820

Signed by Michael Mileski
Surveyor's Michigan License No. 39091

Date 23 Dec 1997

